

Written examination (multiple choice questions) for the post of "Station Master"(25%GENERAL SELECTION) from Points Man in SECUNDERABAD division
Multiple choice questions:

01. Authorized officer for South Central Railway is:[]
 A) PCOM B) PCE C) PCCM D) CSO
02. General Manager of South Central Railway is:[]
 A) Sri. G. Mallya B) Sri.V.N.Mathur C) Sri.M.S.Jayanth D) Sri.G.N.Asthana.
03. Life of a detonator can be extended for -----no. of years after the expiry of normal life []
 A) 4 B) 3 C) 5 D) 2
04. Paper Line Clear Ticket for Up trains is: []
 A) T/B.1425 B) T/D.1425 C) T/C.1425 D) T/A.1425
05. Fog Signal Post is erected at a distance of -----meters in rear of First stop signal []
 A) 270 B) 180 C) 120 D) 250
06. Whose specific orders should be obtained for Running of goods train without Guard? []
 A) Sr.DOM B) CPTM C) Sr.DCM D) PCOM
07. The fixed stop signal of a station controlling the entry of trains into the next block section is []
 A) LSS(Last Stop Signal) B) FSS(First Stop Signal) C) Starter D) IBS
08. Authority to proceed for material train returning to originating station []
 A) T/A.462 B) T/465 C) T/462 D) T/A.465
09. The line ordinarily used for running trains through and between stations []
 A)Goods loop B) Loop line C) Siding line D) Main line
10. When was South Central Railway formed? []
 A) 02.10.1966 B) 16.04.1956 C) 12.10.1965 D) 01.04.2003
11. Repeating signal is a []
 A) Reception signals B) Other signal C) Subsidiary signal D) Dispatch signal.
12. Authority to dispatch Motor trolley(independent)----- []
 A) T/A 1525 B)T/1525 C) T/1708 D)T/1425
13. The Speed Restriction of Motor trolley while running over points and crossings is :[]
 A)20 Kmph B) 30 Kmph C) 10 Kmph D) 15 Kmph
14. The maximum no. of men that may be carried on a Motor trolley shall not exceed on B.G []
 A) 5 B) 10 C) 8 D) 15
15. Engine shall be stopped at a distance of -----while performing coaching shunting. []
 A) 20 meters. B)10 meters C) 15 meters D) 12 meters

16. Shunting with man power is called as----- []
 A) Flat shunting. B) Hand shunting C) Fly shunting D) Loose shunting
17. What is the Speed restriction to be followed while tank wagons are shunting? []
 A) 5Kmph B) 8 Kmph C) 10Kmph D) 15 Kmph
18. Gate signal is identified with ----- []
 A) P marker B) G marker C) R marker D) S marker
19. When rail breakage is upto 30mm. First train to observe Speed Restriction is----- []
 A) 5 Kmph B) 8 Kmph C) 10 Kmph D) 15 Kmph
20. When rail breakage is upto 30mm. Subsequent trains to observe Speed Restriction is ---- []
 A) 5 Kmph B) 8 Kmph C) 10 Kmph D) 15 Kmph
21. South Central Railway is divided into -----no. of divisions []
 A) 5 B) 6 C) 3 D) 4
22. Head quarters of South western Railway-----[]
 A) Bangalore. B) Hubli C) Bilaspur D) Belgaum
23. Expand CRS:[]
 A) Commissioner Rolling Stock B) Chief Railway Secretary
 C) Commissioner of Railway Safety D) Chief Railway Superintendent
24. Headquarters of RDSO----- []
 A) Lucknow. B) New Delhi C) Mumbai D) Hyderabad
25. Distance between two rails in a Broadgauge(B.G) []
 A) 1676 meters B) 1.676 centimeters C) 1.676 millimeters D) 1.676 meters.
26. General Rules are framed by []
 [A] Railway Board [B] Authorized Officer [C] General Manager [D] PCOM
27. Approved special instructions are issued or approved by []
 [A] PCOM [B] Authorized Officer [C] CRS [D] Railway Board
28. Home signal lever / switch will be normalized after passage of the []
 (A) Engine (B) whole train (C) first vehicle (D) none of these
29. Before the arrival of the train, to avoid complaints from road users, taking off the approach Stop signals can be delayed to ensure that gate is closed only for []
 [A] 20 minutes [B] 10 minutes [C] 15 minutes [D] 30 minutes
30. A signal taken "OFF" for a train can be put back to "ON" position in emergency only to []
 (A) obey SCOR instructions (B) obey Station Master's instructions
 (C) issue tickets (D) Avert an accident

31. After putting back starter/advanced starter for a departing train, LP of the train should be advised through a []
 (A) Written memo (B) C.O. (C) T / 369 (3b) (D) none of above
32. The normal aspect of a fixed signal, except Automatic Signals is []
 [A] Attention [B] caution [C] proceed [D] most restrictive
33. Even though departure signals are taken off, LP shall stop at stations where stoppages are scheduled in the []
 [A] VG [B] CTR [C] WTT [D] SOB
34. The points on single line, that must be set against the blocked line, immediately after the arrival of a train at the station []
 (A) Rear (B) front (C) either end (D) none of above
35. The points on double line, that must be set against the blocked line, immediately after the arrival of a train at the station []
 (A) Rear (B) front (C) either end (D) none of above
36. When all the lines at a station are blocked by passenger carrying trains, and still line clear is granted for a train, the points shall be set for the line occupied by []
 (A) Main line & engine facing (B) Loop line & engine facing
 (C) Main line & SLR facing (D) Loop line & SLR facing
37. The indications that must be checked by the SM to see that the points are in working condition after the operation of every motor operated point are []
 (A) "N" (B) " R " (C) either A or B (D) none of the above
38. On Single Line, the Signal over lap shall be reckoned from []
 (A) Facing points (B) trailing points (C) facing end points (D) Home signal
39. On Single line in MAS, the Signal Over Lap shall not be less than []
 (A) 100 m (B) 110 m (C) 120 m (D) 150 m
40. The signals that are prohibited to be used for shunting purposes are []
 (A) Outer (B) Home (C) LSS (D) All the above
41. The provision of catch siding is compulsory, where the falling gradient towards station is steeper than []
 [A] 1 in 80 [B] 1 in 100 [C] 1 in 260 [D] 1 in 400
42. The provision of slip siding is compulsory, where the falling gradient towards block section is steeper than []
 [A] 1 in 80 [B] 1 in 100 [C] 1 in 260 [D] 1 in 400
43. All points shall normally be set for the []
 [A] loop line [B] turn out [C] straight line [D] any line

44. The notice that SM shall ensure whenever points /signals/ Block Instrument is disconnected by SI / ESM is[]
 A) Reconnection notice B) Disconnection notice C) failure memo D)noneof these
45. Whenever the points / signals / block instruments are disconnected , S M shall inform Cabin Man / C ASM / SWM under exchange of []
 [A] Message [B] PN [C] verbal order [D] intimation not necessary
46. Before reconnecting the Signal gear that is disconnected, SI/ESM shall test jointly with[]
 [A] TI [B] S&T khalasi [C] PointsMen [D] SM on duty
47. From the time of disconnection to reconnection, the trains shall be admitted by []
 [A] Hand signals [B] fixed signals [C] piloting [D] none of above
48. While accepting Disconnection Notice for block instrument the SM shall endorse on the Notice that
 [A] Block Section is occupied [B] block section is free [C] Block instruments failed [D]
 None of the above
49. Whenever signal Inspector is testing the signal, the remarks shall be recorded in []
 [A] TSR [B] Station Diary [C] PN exchange book [D] S & T failure register
50. Violently waving a white light horizontally across the body of a person indicates []
 [A]train parting [B] move away from the person signaling [C] proceed [D] stop dead
51. Detonators are also known as []
 [A] Fog signals [B] flare signals
 [C] illuminating signal [D]none of these
52. The number of detonators that are given to each fog signalman is[]
 [A] 8 [B] 10 [C] 20 [D] 24
53. From FSS the FSP is located at a distance of []
 (A) 180m (B) 120m (C) 400m (D) 270m
54. Nominated fog signalmen are two from each department []
 (A) Engineering and S&T (B) Engineering and Operating
 (C)Mechanical and Operating (D) Only from Engineering
55. The Register in which fog signalmen's assurance will be taken is []
 A) TSR B) Station Detonator Register C) Station diary D)SWR assurance
56. Testing of detonator shall be done by moving an empty wagon hauled by a locomotive at a speed of[]
 A) 11 to 13kmph B) 15 to 20 kmph C) 8 to 11kmph D) 12 to 15 kmph
57. No. of detonators which shall be kept in stock at a station, is prescribed by[]
 [A] DRM [B] DOM [C] PCOM [D] DEN

58. The knowledge of staff that are required to use detonators shall be tested once in []
[A] One month [B] two months [C] three months [D] six months
59. TI/SM/PWI shall test detonators once in []
[A] 3 months [B] 6 months [C] 8 months [D] 12 months
60. Normal life of a detonator manufactured before 2010 is []
[A] 3 years [B] 5 years [C] 7 years [D] No limit
61. Normal life of a detonator manufactured during 2010 and thereafter is []
[A] 3 years [B] 5 years [C] 7 years [D] No limit
62. The maximum number of extensions after successful testing of a detonator is []
[A] one [B] two [C] three [D] any number
63. The signals used to warn the incoming train, of an obstruction during day shall be a []
(A) flashing Amber light (B) red flag (C) Red light of H/S lamp (D) red flashing H/S Lamp
64. Whenever a signal/point/block instrument is defective, SM shall make an entry in []
(A) S&T failure register (B) PN exchange register
(C) relay room key register (D) crank handle register
65. Whenever a signal which is detecting a point becomes defective, these points shall be treated as []
(A) interlocked (B) non interlocked (C) working (D) none of above
66. A blank signal under complete power off situation is to be treated as []
(A) Defective signal (B) signal at off (C) no signal (D) none of above
67. Pre-warning about a defective reception signal is not required when there is a / an []
(A) Calling on signal (B) Adv. Starter (C) Isolation (D) none of above
68. When pre warning is given about a defective Home signal, the LP may pass such signal on receipt of []
[A] PHS at the foot of the defective signal [B] PHS at the first facing points
[C] T.369 (3b) + PHS [D] PN through SPT
69. Before granting line clear, at a class 'A' station, Line shall be clear up to (beyond FSS) []
A) Starter B) NLT 400 meters C) either A or B D) none of above
70. Advance authority to pass defective Reception signal is []
[A] T.369 (3b) [B] T.369 (1) [C] T/C.1425 [D] T.409
71. When a train is received on Calling ON signal, cancellation in Podanur panel takes []
[A] 120 seconds [B] 180 seconds [C] 240 seconds [D] 90 seconds
72. The axle counter shall be reset only after ensuring that the monitored portion is []
[A] Vacant [B] occupied [C] obstructed [D] none of above

73. Whenever axle counters provided for loop line are to be reset , it should be done by S M on duty along with one []
A) Operating official B) S & T official C) A or B D) none of above
74. Authority to pass defective starter signal (if it is not LSS) is[]
A) Calling on signal taken off B) T.369(3b)+ PHS C) A or B D) P L C T
75. The authority given to the LP, when I B distant signal fails in "OFF" position, before dispatching[]
A) P L C T B) T / 369 (3b) C) P L C T + T.369(3b) D) none of above
76. On Double line when LSS is defective , Authority to proceed is []
[A] T / 369 (3b) [B] P L C T [C] T / 806+PN [D] T/C.602
77. On Single line token less section, when LSS is defective Authority to proceed is[]
[A] T / 369(3b) [B] T/B.602 [C] T.806+PN [D] P L C T
78. The authority required by Loco Pilot when passes starter at "ON" partly & stopped before Advanced Starter[]
(A) Memo countersigned by Guard (B) T.369 (3b) + PHS
(C) Advanced starter taken off / PLCT (D) all the above
79. Gate-cum-Distant signal shall be located in rear of the gate at a distance of not less than []
[A] 90 meters [B] 120 meters [C] 180 meters [D] 350 meters
80. If a signal is showing white light in place of a color light, it is treated as showing []
(A) most restrictive aspect (B) caution (C) attention (D) Proceed
81. The signal shall be treated as defective, whenever color light signal is flickering / bobbing and does not assume a steady aspect for at least []
[A] 20 seconds [B] 30 seconds [C] 60 seconds [D]120 seconds
82. The authority given to the loco pilot at station, when I B S is defective []
(A) P L C T (B) T / 369 (3b) (C) Both A& B (D) none of above
83. In case the IBS, which is interlocked with L.C. Gate, becomes defective, SM shall []
[A] Treat the LC gate as closed [B] treat the LC Gate as non-interlocked
[C] exchange PN with the Gateman [D] both 'B' and 'C'
84. The facility that is provided on an I B signal post is []
[A] Phone connecting the rear SM [B] Phone connecting the advance SM
[C] Phone connecting the SCOR [D] Phone connecting the TPC
85. When I B S is at `ON`, the Loco Pilot shall stop in rear of the signal and contact []
A) SM in advance B) SCOR C) SM in rear D) TPC
86. When IBS is at "ON" and the telephone is out of order, Loco Pilot after waiting for five minutes shall proceed when view is clear/not clear upto next stop signal at a speed not exceeding [] 6
A) 10/ 8kmph B) 25/ 10kmph C)20/ 10kmph D)15/ 8kmph

87. The button to be operated by S M rear , to reset Analog axle counter, if I B S fails due to improper counting[]
[A] PB-1 [B] PB-2 [C] PB-3 [D] PB-4
88. Wherever I B S is provided, LSS is interlocked with []
(A) Axle counters (B) Block Instrument (C) IBS (D) trailing points
89. In I B S area , the I B Signal is interlocked with []
(A) Axle counters (B) Block Instrument (C) LSS (D) trailing points
90. The indication that appear at the SM in rear, when Loco Pilot passes I B S at 'ON'[]
[A] K1 [B] K2 [C] K3 [D] K4
91. The indication that appear ,when Loco Pilot passes LSS in 'OFF' position is[]
A) K1 B) K2 C) K3 D) K4
92. When Loco Pilot passes LSS in OFF position, K2 indication will appear which will become normal by putting back []
A) FSS knob/lever B) LSS knob/lever C) Gate key knob/lever D) IBS knob/lever
93. The indication that will appear when Loco Pilot passes IBS in "OFF" position is []
A) K1 B) K2 C) K3 D) K4
94. When Loco Pilot passes IBS in OFF position, K3 indication will appear which will become normal, by putting back []
A) FSS knob/lever B) LSS knob/lever C) Gate key knob/lever D) IBS knob/lever
95. The indication that appear, along with buzzer, whenever I B S or I B distant signal bulb is fused is []
[A] K1 [B] K2 [C] K3 [D] K4
96. Over the trailed through points, under no circumstances should a train be []
[A] Move forward [B] backed [C] Run with MPS [D] none of these
97. The control office should advise the standard time daily by a general call to the stations at []
[A] 08.00 hours [B] 16.00 hours [C] 00.00 hours [D] none of these
98. All S Ms should correct the time at 16.00 hrs and make an entry in the []
(A) T S R / Station Diary (B) S&T failure register
(C) Attendance registers (D) PN exchange register
99. ODC shall be allowed to be attached by a train for transport only with prior sanction of []
[A] CRS [B] RAILWAY BOARD [C] TXR [D] PCOM
100. During dense fog maximum speed of a train on Absolute block system shall be restricted to (When loco not fittedwith fog signal device)[]
A) 25kmph B) 8kmph C) 60 kmph D) 20kmph

101. Normally the speed of trains over Non-Interlocked points, turnouts and crossover shall not exceed []
[A] 8 kmph [B] 10 KMPH [C] 15 KMPH [D] 30 KMPH
102. The maximum speed of a train on 1 in 8 ½ turnout (symmetrical split, Thick Web switch of 52/60 kg rails on PSC sleepers and on PSC sleepers is restricted to []
[A] 8 kmph [B] 10 KMPH [C] 15 KMPH [D] 30 KMPH
103. The speed of a train on 1 in 8½ turnout (curved switch of 52/60 km rails) on PSC sleepers is restricted to []
[A] 8 kmph [B] 10 KMPH [C] 15 KMPH [D] 30 KMPH
104. Isolation is necessary, where the trains are permitted to run through the station at a speed exceeding []
[A] 50 kmph [B] 110 KMPH [C] 75 KMPH [D] 15 KMPH
105. Engine pushing is permitted with the prior permission of []
(A) SM in advance (B) SM in rear (C) SM of the notice station (D) None of above
106. When engine is pushing a train without Guard, the duties of Guard deploys on []
[A] Points Man [B] ALP [C] S M [D] none of these
107. The colour of marker lights on both sides of engine exclusively deployed for shunting purpose shall be []
[A] White [B] Red [C] amber [D] red and yellow
108. When head light is defective after putting marker lights 'on' train can go with a speed not exceeding []
(A) 40kmph (B) Severest temporary speed restriction in the block section
(C) A or B whichever is less (D) none of above
109. Last vehicle indicator during night shall be []
[A] L.V board of approved design [B] Retro reflective L.V board
[C] Red flashing light [D] red flag
110. Normally, Side lights shall show towards the train engine []
(A) Red colour (B) white colour (C) green colour (D) yellow colour
111. Side lights may be dispensed with, for []
(A) E M U (B) Goods trains (C) Express trains (D) Both A & B
112. What shall be fixed behind an assisting engine when it is attached in rear of a train? []
(A) Tail board (B) Tail lamp (C) either A or B (D) Flasher Light
113. It will be the duty of the Guard to ensure that , the last vehicle in rear is affixed with []
(A) Tail lamp (B) Tail board (C) Red flag (D) either A & B
114. Light engines or coupled engines (in rear)shall have []

(A) Tail board (B) Tail lamp (C) Red marker lights (D) white marker lights

115. The bell signal that SM has to give, when he observes a train passed without tail lamp/tail board (to station in rear) where B P A C is not provided . []
 A) Six pause one B) Six pause two C) Six pause three D) Six pause four
116. The bell signal that SM has to give , when he observes a train passed without tail lamp/tail board (to station in advance) where BPAC is not provided.[]
 A) Six pause one B) Six pause two C) Six pause three D) Six pause four
117. When SM observes a train passed without tail lamp/tail board (where BPAC is not provided), shall stop all the trains proceeding on adjacent line and issue []
 (A) P L C T (B) T / 369 (3b) (C) caution order (D) verbal orders
118. Guard shall report to the Station Master of the next important station, any stoppage or other irregularities in train working and record the details in CTR and send a special report to []
 A) DOM B) DME C) DRM D) DSC
119. The full form of O T L (BV equipment) is []
 (A) over time leave (B) one time lock (C) one time leak (D) one time lever
120. Dy.SS/TNC of the originating station shall record the intactness and availability of the BV equipment in the register and obtain acknowledgement of []
 [A] Guard [B] S.E (C&W) [C] LP when without guard [D] all the above
121. Periodical replacement of Fire Extinguishers shall be done once in []
 [A] 3 months [B] 6 month [C] 12 months [D] 3 years
122. At destination station, Guard shall obtain acknowledgement about the intactness of OTL and seal of Dy.SS or SE / JE-C&W in the []
 [A] Rough journal or VG [B] CTR [C] LTM [D] RS-5
123. In case of emergency the Assistant Loco Pilot can be authorized to drive the train up to the nearest point where he can be relieved (speed not exceeding) []
 A) 30kmph B) 40kmph C) 60kmph D) MPS
124. Maximum No. of officials / staff, including engine crew at any time on the engine (except in emergencies) []
 [A] 2 [B] 3 [C] 5 [D] 6
125. The number of persons permitted to travel in the brake-van of goods trains, including Guard, should not exceed []
 [A] 2 [B] 3 [C] 5 [D] 6
126. In an emergency, a goods train without brake van can be ordered by []
 (A) Sr.DOM (B) DOM (C) DRM (D) either A or B

127. Maximum number of coaches in addition to the officers inspection coach can be attached in rear of SLR of a Passenger & Mail / Express trains []
[A] 1 [B] 2 [C] 3 [D] 5
128. Maximum number of bogies (or its equivalent) attached in rear of the rear brake van by a goods train is []
[A] 1 [B] 2 [C] 3 [D] 5
129. Maximum number of damaged vehicle / engine allowed by a goods train. []
[A] 1 [B] 2 [C] 4 [D] any number
130. Damaged vehicle/engine shall be attached to a goods train by SM, only on receipt of written advise in duplicate from []
(A) TXR (B) SSE / loco (C) either A or B (D) none of these
131. Whenever vehicles are attached / detached on a train , at an intermediate station the entries in the VG must be made by []
A) Guard B) Station staff C) Loco Pilot D) none of these
132. In an emergency, a goods train without Guard can be ordered by []
[A] SM [B] Dy. CHC [C] Sr. DOM [D] DOM
133. In multi pilot system to start the train from siding the authority is []
A) written authority issued by SM, B) written authority issued by siding authority
C) Written authority issued by pilot in-charge D) none of the above.
134. The intimation , through which Station Master advises the Loco Pilot with necessary endorsement , stating that the train is to run without Guard is []
A) Verbal orders B) train notice C) train order D) caution order
135. Where IBS is provided, the SM shall not dispatch a train in rear of train running without Guard unless it reaches the []
A) IBS B) First stop signal C) next block station D) none of these
136. In Automatic block territory, no train shall be allowed to follow a train without brake van / Guard , until it arrives complete at the next []
A) Reporting station B) Junction station C) Automatic signal D) Gate lodge
137. Running of a goods train without Guard, is strictly prohibited during []
[A] Tempestuous weather [B] total interruption of communications
[C] Temporary single line working [D] all the above
138. When SM receives an advice of Hot axle on a train, it shall preferably be admitted on []
[A] Line provided with sand hump [B] loop line [C] Main line [D] none of these
139. The check that shall be conducted, while clearing stabled stock from a station / invalid BPC, is []
A) Guard and SM B) LP and SM C) Guard and LP D) SM, Guard & LP

140. The test that shall be conducted, whenever train engine is changed, is []
A) Brake continuity B) GLP check C) brake power D) feel test
141. Time permitted for GLP check of a train consisting of 60 units is []
[A] 20 minutes [B] 60 minutes [C] 45 minutes [D] 30 minutes
142. Time permitted for GLP check of a train working without Guard consisting of 60 units is []
[A] 20 minutes [B] 60 minutes [C] 45 minutes [D] 30 minutes
143. While at station, the Loco Pilot is to obey the orders of []
[A] GD [B] TLC [C] LI [D] SM
144. The validity of CC rake BPC is []
A) 35 days B) 7500 KM C) A or B whichever is earlier D) none of these
145. The validity of Premium rake BPC is []
[A] Till destination [B] 12 days [C] 30 days [D] 35 days
146. The grace period given for end to end rake BPC is []
(A) one day (B) two days (C) three days (D) four days
147. The validity of End to end BPC is []
(A) 12+3 day (B) loading point to destination
(C) TXR point to destination (D) two TXR checking points
148. S M shall arrange Points Man to show all right signals for a run through train from []
[A] Station side [B] off side [C] any side as per convenience [D] none of these
149. The following are exempted from exchanging 'All right' signals []
[A] LP of DMU / EMU [B] LP of a train W/O guard
[C] Guards of Super fast trains [D] none of these
150. The time allowed normally to goods trains to start , after engines have been attached is not more than []
(A) 20 minutes (B) 30 minutes (C) 45 minutes (D) 60 minutes
151. The time allowed to goods trains to start after engines have been attached in case of formations tested by Vacuum Exhausters/Air-Compressors, shall not exceed []
(A) 20 minutes (B) 30 minutes (C) 45 minutes (D) 60 minutes
152. Fresh B P C is required when train is stabled at a station (other than loading and unloading station for more than []
[A] 72 hours [B] 24 hours [C] seven days [D] four days
153. Fresh B P C is required whenever (eight-wheeler) vehicles are attached or detached, to / from a goods train by more than []

[A] 10 [B] 4 [C] one [D] 10% of total wagons

154. The effective brake power in case of Mail/Express at the originating station shall be 100% and en route should be not less than []
(A) 100% (B) 95% (C) 90% (D) not specified
155. When a train is held up at FSS, the Loco Pilot shall depute his Assistant Loco Pilot to go to Station, after []
[A] 10 minutes [B] 15 minutes [C] 5 minutes [D] none of these
156. While working a passenger train , the Loco Pilot shall ensure that the passenger bogies do not over shoot []
[A] platform [B] FSS [C] Sand hump [D] none of these
157. The whistle code, that is given by the Loco Pilot when SM / Station Staff does not exchange ' all-right' signals is []
(A) 00 (B) 000 (C) __0 __0 (D) 00__
158. When engine whistle fails on run, after clearing block section cautiously , L P shall []
[A] Continue with 40 kmph [B] Advise PRC/TLC and act accordingly
[C] Ask for repair or relief [D] none of these
159. Whistle code while ` Passing Signal at ON with proper Authority []
(A) 0 - 0 (B) 0 0 - (C) _ 0 _ (D) _ 0 0
160. Engine whistle code 0 0 - indicates []
(A) Insufficient air pressure in engine (B) alarm chain pulled
(C) either A or B (D) Passing signal at On with proper authority
161. Whenever train stopped without clearing fouling mark, to prevent any movement on the fouled line the Guard shall inform the SM at once by []
(A) showing green flag (B) waving white light
(C) exchange of P N (D) exhibiting stop hand signal
162. Material train shall be ordered to work with the permission of []
[A] DRM [B] DOM [C] PCOM [D] DEN
163. To dispatch a material train for working in the block section and return to the same station, authority given to the LP is []
[A] PLCT [B] ATP W/O line clear [C] T/462 [D] T/A.462
164. The authority given to the LP of a material train for working in the block section and proceed to the next station is []
A) T / 462 B) T/A 462 C) T / 465 D) none of these
165. The validity of a material train B P C , is []
A) 30 days B) 21 days C) 15 days D) none of these

166. The effective brake power of a material train shall be (not less than) []
 [A] 100 % [B] 85% [C] 90 % [D] 95 %
167. Responsibility of stabling a material train at a station, lies with []
 A) Guard B) Station Master C) SM & Guard D) Guard and PWI
168. The maximum speed of a T T M is []
 A) 10kmph B) 20kmph C) 30kmph D) 40kmph
169. The maximum speed of a T TM , over points and crossing is []
 A) 10kmph B) 20kmph C) 30kmph D) 40kmph
170. TTM is permitted to work in the block section only during []
 A) line block B) integrated block C) shadow block D) all the above
171. When TTMs are following each other, the speed of the second TTM is restricted to []
 [A] 25/10 kmph [B] 15/10 kmph [C] 15/8 kmph [D] no restriction
172. The officials to sign and issue the GWR of Non- Interlocked gates are []
 (A) DOM & DEN (B) DSTE & DEN (C) DOM & DSO (D) DOM & DSTE
173. SWR diagram must be signed by []
 [A] DEN & DEE [B] DSTE & DOM [C] DOM, DSTE & DEN [D] T I & SSE(SIG)
174. Appendix 'G' (rules for electrified section) of SWR must be signed by []
 [A] DOM&DSTE [B] DOM & DEN [C] DOM ,DSTE & DEE [D] TI& SSE(SIG)
175. SWR should be issued afresh , once in []
 [A] 3 years [B] 5 years [C] one year after completion of half years [D] 10 years
176. After issue of following number of amendment slips, SWR shall be issued afresh []
 [A] 3 [B] 4 [C] 5 [D] 7
177. Fresh declaration shall be obtained from a member of staff in the following case []
 [A] when newly joined at station
 [B] Resumes duty after an absence of 15 consecutive days or more.
 [C] any change in the SWR
 [D] Any of the above
178. The following form shall not be issued in manuscript []
 [A] T/D 1425 [B] T/369(3b) [C] T/462 [D] T/409
179. Written authority , to receive a train on to an obstructed line []
 [A] T/511 [B] pilot in memo [C] T/369(3b) [D] T/509
180. While receiving a train on to an obstructed line, Stop hand signal shall be exhibited from the point of obstruction at a distance of (not less than) []
 (A) 45 meters (B) 20 meters (C) 120 meters (D) 180 meters

181. Written authority to start a train from a station having common starter, is []
 [A] T/511 [B] pilot out memo [C] T/512 [D] T/509
182. The speed during shunting operations shall not exceed []
 [A] 10 kmph [B] 15kmph [C] 30 kmph [D] 8 kmph
183. Slip coaches shall not be kept on a blocked line in the rear of a []
 [A] Passenger carrying train [B] light engine [C] shunting engine [D] stabled load
184. While performing shunting on passenger carrying trains, the shunting engine before coming on to the formation should be stopped before the formation at a distance of []
 [A] 45 meters [B] 20 meters [C] 15 meters [D] 10 meters
185. At a station where separate shunting staff are not employed, shunting operations shall personally be supervised by []
 [A] Points Man [B] Loco pilot [C] SM [D] Guard
186. While backing a full train from one line to another via main line, shunting supervision shall be done by []
 [A] Points Man [B] Loco pilot [C] SM [D] Guard
187. Carriages containing passengers shall not be moved for shunting purpose without the personal orders of the []
 (A) SM& LP (B)GD &SM (C) GD (D) GD&LP
188. While performing shunting, the points which are not protected by signals must be locked by Following methods []
 [A] Clamped and padlocked [B] cotter bolted and padlocked
 [C] Either A or B [D] none of these
189. While shunting wagons containing explosives, the supervision shall be done by []
 [A] Points Man [B] Loco Pilot [C] S M [D] Guard
190. The maximum speed while shunting of wagons containing explosives and P O L products shall be []
 [A] 10 kmph [B] 15kmph [C] 30 kmph [D] 8 kmph
191. Where shunting operations are supervised by Guard/SM, Loco Pilot shall be given []
 [A] T/A 806 [B] written memo [C] T/806 [D] T/409
192. The gradient that is considered as steep gradient for the purpose of shunting , roller bearing wagons []
 [A] 1 in 400 [B] 1 in 600 [C] 1 in 260 [D] 1 in 150
193. Shunting of roller bearing vehicle on a steep gradient shall be done only with locomotive attached towards the []
 [A] As per convenience [B] falling gradient [C] Raising gradient [D] none of these

194. While stabling a goods train having BOX 'N' / BCN / BRH, etc., minimum no. of vehicles hand brake to be applied (in addition to hand brakes of B/V)are []
 [A] 3 from each end [B] six wagons on either side
 [C] nine from each end [D] 10 from engine 5 from B/V
195. When the Loco Pilot of a train experiences any abnormal condition on the track, shall stop his train at []
 [A] LSS of next station [B] FSS of next station
 [C] Within station section [D] next block station without clearing block section
196. When the Loco Pilot of a train experiences any abnormal condition on the track, in case of IBS / Automatic block territories, shall stop the movement of trains and inform []
 [A] Station Master [B] Loco pilots of following trains
 [C] both A & B [D] none of these
197. When 'lurch' is reported and subsequently a train is sent with engineering official, caution order is given to the LP to []
 [A] stop dead and be guided by Engg.official [B] Run through
 [C] Simply proceed with 10 kmph [D] observe SR of 8 kmph
198. When 'lurch' is reported and subsequently a train is sent in the absence of engineering official, caution order is given to the LP to stop dead if considered safe, proceed at a speed of []
 [A] 10 kmph [B] 15 kmph [C] 30 kmph [D] 8 kmph
199. Rail fracture of less than 30mm, the speed of first train shall be []
 [A] 10 kmph [B] 15kmph [C] 30 kmph [D] 8 kmph
200. Rail fracture of less than 30mm, the speed of second and subsequent trains shall be []
 [A] 10 kmph [B] 15kmph [C] 30 kmph [D] 8 kmph
201. Rail fracture of more than 30 mm or multiple fractures, track is to be certified by []
 [A] AEN [B] PWI [C] key man [D] Gang mate
202. On Double line the Authority to dispatch a goods train against the established direction of traffic for any reason (other than introduction of TSL working) is []
 [A] C L C T [B] T/J 602 [C] P L C T [D] T/369(3b)
203. During T S L working , the block instruments shall be kept and locked in []
 [A] T O L position [B] Line closed position
 [C] Line clear position [D] TOL position for wrong line trains only
204. During Temporary Single Line working, the written Authority given to Loco Pilot is []
 [A] P L C T [B] C L C T [C] T/D 602 [D] T/369(3b)
205. During T S L working, the speed of first train shall be []
 [A] 25 kmph [B] 10 [C] 15 [D] MPS
206. During T S L working the speed of second and subsequent trains shall be []

[A] 25 kmph [B] 10 [C] 15 [D] M P S

207. During TSL working when the train is proceeding on wrong line, in addition to ATP, the train shall be dispatched by issuing []
[A] pilot out memo [B] T/369(3b) [C] T/511 [D] T/512
208. Authority for light engine, going to open communications shall be []
[A] T/A 602 [B] T/B 602 [C] T/C 602 [D] T/D 602
209. Maximum permissible speed of a goods train loaded with CC+8+2 is-----
[A] 60 KMPH B] 30 KMPH [C] 40 KMPH [D] 750KMPH
210. The speed of the Light engine going for opening of communication shall be []
[A] 15/10 kmph [B] 10/8 kmph [C] normal speed [D] 25 kmph
211. After opening communication, the light engine shall return on []
[A] C L C M [B] P L C T [C] T/B 602 [D] C L C T
212. For line block purpose, the engineering works are divided into --- categories
A] 5 B] 3 [C] 7 [D] 4
213. Down CLCT is prepared on Form No : []
[A] T/D 1425 [B] T/G 602 [C] T/H 602 [D] T/F 602
214. When there is an even flow of trains, enquiry and reply messages are sent through []
[A] Loco Pilots [B] SM off duty [C] Points Men [D] Guards
215. After opening communication, the speed of the first train (waiting) shall be []
[A] 25/10 kmph [B] 15/10 kmph [C] normal speed [D] 15/8 kmph
216. Once communication is restored, the Station Master must send a message to the SM of adjacent station in the prescribed form on []
[A] T/E 602 [B] T/G 602 [C] T/H 602 [D] T/I 602
217. Written authority to dispatch a relief engine into an obstructed block section, is []
[A] T/A 602 [B] T/B 602 [C] T/C 602 [D] T/D 602
218. S M shall arrange to send a competent railway servant, if a passenger / goods train does not turn up, even after the normal running time and ----- []
[A] 5/10 minutes B] 10/20 minutes [C] 20/30 minutes [D] 15/25 minutes
219. If Loco Pilot enters block section without A T P and subsequently sends his ALP with a memo to SM in rear, that S M shall arrange to send []
[A] P L C T [B] Caution order [C] T/A 602 [D] T/369(3b)
220. If Loco Pilot enters block section without A T P and subsequently sends his ALP with a memo to SM in advance, that S M shall arrange to send []

[A] P L C T [B] Caution order [C] T/A 602 [D] T/369(3b)

221. If a train parts and the Loco Pilot decided to proceed to the station ahead, he shall, on approaching the station give the following whistle code []
 A) _ _ 00 [B] _ 0 _ 0 [C] _ 00 [D] 0 _ 0
222. During divided train working, the written authority issued by the Guard of the train , to the L P to clear the first portion is []
 [A] T/A 602 [B] Caution order [C] T/609 [D] Written memo
223. When a goods Train runs without Guard has to be divided, the Loco Pilot shall bring first portion by preparing
 [A] T/A.602 [B] Caution order [C] T/609 [D] Written memo
224. When a train without Guard is divided in the section, after dropping the first portion, light engine returning to pickup second portion shall proceed on authority []
 [A] T/A.602 [B] Caution order [C] T/609 [D] Written memo
225. On Absolute Block System, no train shall be allowed to leave a block station unless, the following has been received from advance Block station []
 [A] Authority to Proceed [B] line clear [C] consent [D] information
226. On Absolute block system, the adequate distance (BOL) beyond FSS on M A S for granting line clear shall not be less than []
 [A] 180 meters [B] 120 meters [C] 400 meters [D] 100 meters
227. At a class 'B' station on D/L equipped with MACLS, to grant line clear, the line must be clear up to
 [A] S L B [B] BSLB / outermost facing points [C] Adv. starter [D] starter
228. At a class 'B' station on S/L equipped with MACLS, to grant line clear, the line must be clear up to
 [A] S L B [B] outermost facing points [C] Opposite Adv. Starter [D] any of the above
229. At a class 'C' station, line clear shall not be given unless, the whole of the last preceding train has passed complete at least 400 meters beyond the Home signal and []
 [A] Continuing its journey [B] clears advance block section also
 [C] Condition for taking home signal also fulfilled [D] all the above
230. Running of trains In SCR is permitted with maximum no. of coaches
 [A] 18+VPU [B] 23+VPU [C] 26 [D] 24 + VPU/IC
231. The Ministry of Railways Launched a programme for all Railway staff to improve their competence. []
 (A) Rail Vision (B) Rail Vikas Shibir (C) Saksham (D) Rail Swachhta Pakhwada
232. In automatic block system the line between the block stations, when required, be divided into a series of []
 [A] Automatic block signaling sections [B] block sections
 [C] station sections [D] all the above

233. On D/L , the automatic signal shall not assume OFF position ,unless the line is clear not only up to the next Automatic signal ,but also for an adequate distance of (not less than) []
 [A]180 meters [B] 120 meters [C]400 meters [D] 100 meters
234. Automatic signal is identified by []
 [A] 'A' marker [B] Illuminated 'A' marker [C] 'C' marker [D] "AB" marker
235. Semi automatic signal when working as automatic signal is identified by[]
 [A] 'A' marker board [B] illuminated 'A' marker [C] both A & B [D]none of these
236. Normal aspect of Automatic signal is []
 [A] Stop [B] Attention [C] Proceed [D] Most restrictive aspect
237. SMR/TI shall renew the competency certificates (in Automatic section) for []
 [A]SMs [B] Guards of that station [C] SMs and points men [D] none of these
238. When Loco Pilot passes an automatic stop signal at ON, he shall observe speed restriction of []
 [A] 10 kmph when view is clear and 8 kmph in night
 [B] 15kmph when view is clear and 8 kmph when view is not clear
 [C] 10 kmph
 [D] 15 kmph when view is clear and 10 kmph in night
239. When LSS fails on single line automatic block system, Loco Pilot shall be given[]
 [A] P L C T [B] P L C T + T/A 912 [C] PLCT+T/ B 912 [D] T/369(3b) +C.O
240. When LSS fails on double line automatic block system, Loco Pilot shall be given []
 [A] P L C T + C.O [B] P L C T + T/A 912 [C] T/D 912 + T/A 912 [D] T/369(3b) + C.O
241. Authority to dispatch Relief engine/train in obstructed automatic signaling section is []
 [A] T / A 912 [B] T / B 912 [C] T / C 912 [D] T / D 912
242. Relief loco shall proceed with a restricted speed of []
 [A] 25kmph [B] 15 /10 kmph [C] normal speed [D] 15 / 8 kmph
243. Fixed signal which can be operated either as an Automatic signal or a manual signal, is []
 [A] An Automatic stop signal [B] Manual stop signal in automatic territory
 [C] A Semi automatic stop signal [D] A Home signal
244. Gate signal in automatic signaling territory is distinguished by []
 A) G marker and illuminated A marker when gate is closed
 B) Only G marker
 C) G marker and illuminated A marker when gate is open
 D) A marker and illuminated G marker when gate is closed
245. Normal authority to proceed on Single Line token less sections/Double line sections []
 [A] 'OFF' position of LSS [B] PLCT
 [C] PLCT or token [D] Any written document signed by SM

246. At stations provided with block proven axle counter (BPAC) and functioning, The Station Master on duty shall send the "train out of block section" signal only by []
 [A] seeing clear indication of BPAC [B] getting private number from guard
 [C] getting private number from points man [D] listening to LVT buzzer
247. At stations where BPAC is not provided, the Guard of the train, after verifying the last vehicle is standing clear of the fouling mark, shall inform Station Master by []
 [A] Waving arm by day [B] Exchange P N through walkie-talkie
 [C] Showing white light by night [D] none of these
248. Blocking of a portion of line for maintenance work by more than one department is called []
 [A] power block [B] integrated block [C] shadow block [D] no specific name
249. Block availed from either end of the block section, between two block stations simultaneously, is known as []
 [A] Power block [B] Integrated block [C] Shadow block [D] Double block
250. Engineering works come under Category-I II (eg ; Welding of Rail joints) requires []
 [A] Only intimation to SM [B] line block [C] material block [D] Intimation not necessary
251. Engineering branch will arrange with the Operating branch for the issue of a circular notice, which shall be valid for []
 [A] one year [B] 48 hours [C] 3 months [D] six months
252. After issuing circular notice, how many days in advance, the DOM will issue an all concerned message []
 [A] one year [B] 2 days [C] 3 months [D] six months
253. Authorized engineering official to obtain blocks on the field telephone, who shall not be below the rank of []
 [A] Sr.DEN [B] PWI [C] DEN [D] AEN
254. When more than one T/CAR is programmed to go to block section and return to the same station the authorities for first T/CAR and subsequent T/CAR are []
 [A] T/1708, CAUTION ORDER [B] T/A.1708, CAUTION ORDER
 [C] CAUTION ORDER, T/1708 [D] CAUTION ORDER, T/ A1708
255. When more than one T/CAR is programmed to go in the same block section and clear to the next station the authorities for first T/CAR and last T/CAR are []
 [A] T/1708, CAUTION ORDER [B] T/A.1708, CAUTION ORDER
 [C] CAUTION ORDER, T/1708 [D] CAUTION ORDER, T/A1708
256. When more than one TTM is programmed to go in the same block section and return to the same station the authorities for first TTM and subsequent TTM are []
 [A] T/465, CAUTION ORDER [B] T/A.465, CAUTION ORDER
 [C] CAUTION ORDER, T/465 [D] CAUTION ORDER, T/A 465

257. When more than one TTM is programmed to go in the same block section and clear to the next station the authorities for first TTM and last TTM are []
 [A] T/465, CAUTION ORDER [B] T/A.465, CAUTION ORDER
 [C] CAUTION ORDER, T/465 [D] CAUTION ORDER, T/A 465
258. Authority given to the TTM to go into the section work and return to the same station during block is []
 [A] P L C T [B] CAUTION ORDER [C] T/465 [D] T/A 465
259. Authority given to the TTM to go into the section work and proceed to the next station during block is []
 [A] PLCT [B] CAUTION ORDER [C] T/465 [D] T/A.465 []
260. When material train, TTM and Tower wagon are permitted in the same block section to work, the distance to be kept between them shall be []
 [A] 100metres [B] 120metres [C] 150metres [D] 1000metres
261. No. of material trains permitted during the line block/ integrated block/shadow block is / are []
 [A] 1 [B] 2 [C] 3 [D] Any number
262. During line block, to receive the units coming on right line, authority to receive the first unit []
 [A] Home Signal relay [B] pilot in memo [C] T/509 [D] P H S
263. During line block, to receive the units coming on right line, authority to receive the units following the first unit is []
 [A] Take off Home Signal [B] pilot in memo [C] calling on signal or T/509 [D] P H S
264. During line block, the units are coming on wrong line, shall be received on []
 [A] Home Signal [B] pilot in memo [C] Calling on signal [D] P H S
265. When major work such as relaying and re-girding is in progress , a speed restriction that shall be observed on the adjoining line in double line section, is []
 [A] 30 kmph [B] 40 kmph [C] 50 kmph [D] stop dead and proceed
266. When water rises above the ballast level but below rail level, train should be allowed as per following []
 [A] Train shall not be allowed
 [B] Train must stop and proceed after the velocity of the water is reduced.
 [C] Train must stop and be piloted by the PWI.
 [D] Track should be walked over by two men abreast one at either end of the sleepers before the train
267. When water overflows above the rails – []
 [A] Train shall not be allowed
 [B] Train must stop and proceed after the velocity of the water is reduced.
 [C] Train must stop and be piloted by the PWI.
 [D] Train must stop and be piloted by gang man
268. In track circuited areas, trolleys shall have []

[A] Hand brakes [B] brake power certificate [C] insulation [D] none of these

269. In token less section, ATP for the movement of independent motor trolley is []
[A] PLCT [B] T/465 [C] T/1525 [D] T/A 1525
270. On Double line, after the arrival of motor trolley, Station Master shall inform the Station Master of the rear station by []
[A] Giving P.N [B] Putting Block instrument from TOL to 'Line closed' position
[C] Both 'A' and 'B' [D] none
271. When motor trolley is following a full length train or engine or another motor trolley, authority given as A T P is []
[A] T/1525 [B] T/A 1525 [C] ATP without Line Clear [D] P L C T
272. When a Motor Trolley is following a train, it is treated as []
[A] An Independent Train [B] Last vehicle of that train
[C] First vehicle of that train [D] none of these
273. Trolley/Lorry notice: []
[A] T/1518 [B] Circular Notice [C] T/1525 [D] T/A 1525
274. The competency certificate issued by DEE (Tr. D) to S M for operating the isolators (in emergency) is valid for []
[A] 2 years [B] 3 years [C] 4 years [D] 5 years
275. Whenever a tower wagon is to be moved by a train, it should be inside the []
[A] Train engine [B] Rear B / V [C] Sixth Vehicle [D] Any where
276. The maximum speed of tower car shall be []
[A] 40kmph [B] As stenciled on it [C] 30kmph [D] 15kmph
277. When healthy section is temporarily isolated and re-energized, if train entered faulty section, the speed of the first train by (day / night) shall be []
[A] 25/10 kmph [B] 20/10 kmph [C] 40/40 kmph [D] 60/30 kmph
278. During power block, the trains that are allowed to run. []
[A] Diesel hauled [B] electric traction hauled [C] M E M U [D] no train permitted
279. The permission, the Guard of the train with the ODC receives from the authorized person, to enter (in electrified section) is []
[A] Permission from CHC [B] permission from TPC
[C] Trolley / Lorry notice [D] permit to work
280. The notice stations, where divisional caution order shall be issued are specified in []
[A] Working time table [B] rake link [C] CTR [D] Gradient chart
281. In the Caution order, names of the stations concerned should be written in full, but not []
[A] letters [B] Codes [C] Capitals [D] Numerals

282. The caution order should have all the speed restrictions in force in []
 [A] Geological order [B] gradient wise [C] Geographical order [D] control section wise
283. SM shall bring forward the caution orders in the caution order register (in geographical order) []
 [A] Every Shift [B] Every Monday at 00.00 hours
 [C] Everyday at 16.00hrs [D] Everyday 00.00 hrs
284. Record foils of the caution orders shall be preserved for a period of []
 [A] Six Months [B] 3 Months [C] Year [D] 3Years
285. Full form of T V U []
 [A] Train van unit [B] track vehicle unit [C] Train vehicle unit [D] traffic vehicle unit
286. Level crossing gates situated within outermost stop signals of a station are under the control of []
 [A] S E (S&T) [B] S E (PWAY) [C] S M [D] Gate Man
287. At engineering level crossing (interlocked) gate connected to station in advance, if the running time is less than 10 minutes, the Station Master will advise the gateman, the particulars of the train []
 [A] before granting line clear [B] after getting "train entering block section" signal
 [C] when train sighted [D] before seven minutes
288. When the signal protecting the interlocked level crossing gate becomes defective the gate treated as []
 [A] inter locked with signal defective [B] non inter locked
 [C] simply issue C.O to observe gate rules [D] none of above
289. At engineering/traffic level crossing non interlocked gates , S M shall advise Gateman ,about the particulars of the train []
 [A] before granting/obtaining line clear
 [B] Immediately after train entering block section
 [C] before seven minutes if running time is more than 10 minutes
 [D] before seven minutes if running time is less than 10 minutes.
290. If the communication with L C Gate fails, SM shall stop all trains and issue []
 [A] special caution to be alert [B] Authority T/369(3b)
 [C] T/A.602 treating as obstruction [D] caution order to observe gate rules
291. After exchanging PN with gate man, due to change in planning, SM shall inform gate man about cancellation of train movement supported by []
 [A] Private Number [B] written authority
 [C] oral advice [D] None of these
292. The register that staff should also sign, in token of having understood the train working instructions during NI working. []
 [A] Assurance Register [B] Circular notice [C] Special NI working instructions [D] none of these
293. A common NI Home signal provided for any indirect reception of trains, with only []
 [A] stop & caution aspects [B] stop& proceed aspect

[C] Proceed with caution aspect [D] No aspect at all

294. During NI working, all trains must be brought to a stop at the FSS and then allowed to enter (taking off signals) cautiously at speed not exceeding []
[A] As per standard of interlocking [B] 20 kmph [C] 15 kmph [D] 30 kmph
295. During NI working, the LP shall not pass the outermost facing points even though signals are taken off unless he also receives. []
[A] caution order at points [B] PHS at points [C] T/369(3b) [D] none of these
296. During NI working the ASM/Guard/SWM in charge of the goomties shall be responsible for []
[A] exchanging PHS at outermost facing point
[B] correct setting, clamping and pad locking of points
[C] allowing to take off signals when train stopped at the Home signal
[D] All the above
297. Patrolling of railway line is done on following occasions. []
[A] In the event of sudden storm or hurricane during day or night
[B] Security patrolling during civil disorder
[C] Monsoon time
[D] any one of the above.
298. Patrol charts are issued by []
[A] PWI [B] DEN [C] SM [D] PWI & TI
299. Name of night patrolman with arrival and departure timings shall be recorded by SM in []
[A] Beat book [B] Train signal register [C] Station diary [D] All the above
300. If the night patrolman does not turn up even after 15 minutes beyond the schedule arrival time, SM shall stop all the trains and issue caution order restricting the speed to []
[A] 40 kmph [B] Special Caution [C] stop dead and 10kmph [D] stop dead and 15kmph
301. Station Detonator Register contains ---- Parts []
[A] 3 [B] 4 [C] 5 [D] 12
302. In Station Detonator Register, particulars of Fog Signal Men posted at the station from time to time shall be recorded in the []
[A] part-I [B] part-III [C] part-II [D] part-IV
303. Maximum number of wagons containing explosives permitted by goods trains is []
[A] Three [B] Five [C] Ten [D] any number
304. Minimum number of wagons to be given as support wagons from Loco when wagons containing explosives are attached by Goods Train are []
[A] Three [B] five [C] ten [D] one

305. Minimum number of wagons required to be given as support wagons from B V / Passenger coach / other inflammables when explosives are carried by a train []
[A] Three [B] five [C] ten [D] one
306. To attach a dead engine to a train, a certificate of 'fit to run' is required, which shall be issued by []
[A] Section Engineer [B] Power controller [C] Loco Inspector [D] any one of the above
307. Escorting of dead locomotive attached to freight and passenger carrying trains is not necessary []
A) the brakes are fully operational B) attached next to the Train Engine
C) both A & B D) None of the above
308. Number of dead engines is/are permitted to attach to passenger carrying train []
[A] any number each after six coaches [B] one [C] two [D] nil
309. Under any circumstances, no dead engine should be attached to any []
A) Passenger Train B) CC Rake Goods Train C) Rajdhani, Shatabdi/Duranto D) Mail/Express
310. Officers inspection carriages are not to be permitted by []
[A] Race specials [B] Postal express trains [C] Military specials [D] All the above
311. One of the following can be attached in excess of the permitted load. []
[A] Party Coach [B] Parcel Van [C] Officer's Saloon [D] Pantry Car
312. A mail/express train shall have after loco in front and in rearmost at least one []
[A] Brake Van [B] Anti Telescopic or Steel Bodied SLR [C] Saloon [D] Dead Loco
313. When centre S L R is provided in short trains, a maximum number of coaches permitted on either side of S L R []
[A] Three [B] One [C] Two [D] Any No. [E] none of these
314. At standard – I R interlocked station the maximum speed permitted for the train over main line points is []
[A] 50 kmph [B] 75 kmph [C] 15 kmph [D] 110 kmph
315. At standard – II R interlocked station the maximum speed permitted for the train over main line points is []
[A] 140 kmph [B] 75 kmph [C] 160 kmph [D] 110 kmph
316. At standard – III R interlocked station the maximum speed permitted for the train over M L points is []
[A] 140 kmph [B] 75 kmph [C] 160 kmph [D] 110 kmph
317. At standard – IV R interlocked station the maximum speed permitted for the train over main line points is []
[A] 140 kmph [B] 75 kmph [C] 160 kmph [D] 110 kmph
318. After initiation, Route cancellation takes []
[A] 240 seconds [B] 10 seconds [C] 120 seconds [D] 60 seconds

319. After the arrival of the train on calling signal , in Podanur panel the time taken to cancel the same , is []
 [A] 240 seconds [B] 10 seconds [C] 120 seconds [D] 60 seconds
320. Whenever panel is not in use, it should be []
 [A] Switched off [B] locked [C] kept open for operation [D] all the above
321. When power supply fails in Non-electrified area, one generator can be used at a time for a maximum of []
 [A] three hours [B] four hours [C] five hours [D] eight hours
322. Frequent power failures are to be reported to []
 [A] DOM [B] DEE [C] DSTE [D] ESM
323. At the Panel interlocked station, to ensure proper functioning of the emergency cross over Station Master shall test []
 [A] during failure only [B] before each movement [C] every Monday [D] Daily
324. When points are flashing the SM shall ensure that there is []
 [A] free indication [B] route is free [C] no obstruction [D] none of these
325. For resetting the loop line axle counter, the SM shall take the co-operation of staff of []
 [A] optg only [B] S&T only [C] optg or S&T [D] Engg/Optg
326. On Double line, to perform shunting beyond LSS, before giving authority, SM shall []
 [A] Block forward [B] Block back [C] obtain line block [D] none of these
327. On Double line, to perform shunting beyond LSS, authority is []
 [A] T/806 with P.N [B] shunt signal below LSS taken 'off' [C] LSS lever key [D] any one of the above
328. On S/L token less sections, to perform shunting beyond LSS (up to opposite FSS) the authority is []
 [A] T/806 + shunt key or PN [B] shunt signal below LSS taken 'off' [C] T/806 only [D] T/806 + written memo to come back
329. On double line to perform shunting beyond Outer most facing points/BSLB authority is []
 [A] T/806 + P.N [B] T/806+ shunt key [C] T/806 only [D] T/806 + written memo
330. S & T works for maintenance which definitely require Disconnection / Reconnection are grouped under []
 [A] Group -A [B] Group-B [C] Group-C [D] Special Class
331. The Station Master shall hand over the Relay room key to the S&T staff after obtaining the signature in the []
 [A] Station diary [B] Train signal register [C] Relay room key register [D] movement register

332. In SWR, Working of Level Crossing Gates are given in the Appendix []
 [A] 'G' [B] 'B' [C] 'C' [D] 'A'
333. The general precautions regarding OHE (working) of a block station are given in appendix (of SWR)
 [A] 'A' [B] 'B' [C] 'C' [D] 'G'
334. In the event of fire on any part of electrical equipment, the affected part is first to be []
 [A] extinguished by water [B] completely isolated
 [C] Extinguished by mud [D] none of these
335. When Home signal is defective on D/L, to prevent block failure, its lever/knob should be kept In[]
 A)Normal position B)Normal / Reverse position C)Reverse position D)Any Position
336. Bell code to be given to SM in advance, whenever a Train passed without tail lamp or tail board is[]
 A)00000 B)000000 C)000000 – 0 D) 000000 - 00
337. When acknowledgement cannot be obtained for 'Call attention' bell beat, again Call attention shall be given by SM after []
 A) 5 Seconds B)10 Seconds C)20 Seconds D)60 seconds
338. The Station Master taking over charge shall test the block instrument and make a record of the result then and there in the []
 A) Station Diary B)T S R C)S&T Register D).T / 50
339. The Station Master who obtains / grants line clear shall remain on duty till this signal is received/acknowledged. []
 A)Train Out of Block Section B)Train Entering Block Section
 C)Train passed through D)None
340. The TSR shall be retained at station for []
 A) 3 months in which it is completed. B) 6 months in which it is completed.
 C) 1 Year in which it is completed D)1 Year after half year in which it is completed.
341. SM shall test the Podanur push button block instrument /SGE block instrument, without obtaining line clear by attempting to take off []
 A) F S S B) Starter C) L S S D) Any Signal
342. Slip/Catch siding key cannot be removed when Block instrument is in this position. []
 A) TCF B) TGT C) TCF / TGT D) Line Closed
343. In Single line electrified sections ,this type of block instruments are (only) provided. []
 A) P T J B) Kyosan C) Daido D) Any One
344. In push button token less block instrument when shunt key cannot be extracted for shunting purposes, the SM shall advise the SM at the other end []
 A) to keep block instrument in line closed position B) to extract shunt key

C) to keep block instrument in TCF position

D) none of these

345. For all Goods trains at originating station "is line clear" should be asked []
A) Before 5 Min B) Before 10 Min C) after BPC Signed D) when the Train is ready
346. At train starting station , 'is line clear' shall be asked, ---- minutes before the booked departure of the passenger carrying trains. []
A) 5 minutes B) 10 Minutes C) As per W T T D) G D & L P Ready
347. At intermediate stations, for all stopping trains with a halt of less than five minutes 'is line clear' shall be asked when the Train is []
A) Sighted B) Arrived C) As per W T T D) ready
348. For a run through train , is line clear shall be asked ,how many minutes before the train is due to pass []
A) 5 minutes B) 7 minutes C) 10 minutes D) Train left Rear Station
349. For run through trains whose running time is less than seven minutes, Line clear is to be obtained immediately after this signal is received []
A) Train Entering block section B) Is Line Clear C) Train out Of Block section D) None
350. No. of Private Number sheets supplied to each on duty Station Master []
A) One B) Two C) Three D) No limit
351. To prevent Line clear from being taken by the SM of station in advance , in Push button token less block instrument, the SM shall []
A) Remove Shunt Key B) Reverse LSS / FSS knob C) Both A & B D) None
352. When SM does not want to grant line clear, he shall give the following bell code signal []
A) 00000 B) 000000 C) 000000 - 0 D) 00000000000
353. On double line sections when a train is pushed back after entering the block section on normal ATP, the next train shall be dispatched on []
A) Caution Order B) P L C T C) T / 369 (3b) D) Memo
354. When Block forward or Block back is done on double line sections, the block instrument shall be kept in []
A) Locked position B) Line Closed position C) Train On Line position D) TGT / TCF position
355. A relief engine should be sent, if the engine or vehicles running away have not arrived even after a lapse of -----more than the running time of the slowest speed goods train. []
A) 30 min B) 45 min C) 10 Min D) 5 Min
356. When 'Train on line' buzzer fails, the block instrument shall be considered to be interrupted & their working []
A) Partially Failed B) Suspended C) Resumed D) Normal Way

357. Block instrument failure either at station 'X' or station 'Y' shall be recorded by both Station Masters of 'X' and 'Y' in their []
 A) T S R B) S & T Failure Register C) Station Diary D) All the above
358. In the event of failure or suspension of Block Instrument, before signalling a train through any alternative means of communication, both SMs shall exchange Messages and record in the TSR in []
 A) Black Ink B) Red Ink C) Remarks Column D) None
359. When BPAC fails, after resetting the instrument with the cooperation of SM in advance it goes to this mode []
 A) Defective B) Silent C) Preparatory D) Active
360. For issuing P L C T , all trains shall be stopped at []
 A) F S S B) Facing Points C) Starter D) Hand over on Run
361. Even if tail lamp/tail board is not found, closing block section need not be held up if provided with []
 A) Cabins B) Block Instruments C) B P A C D) Panel Board
362. During PLCT working, entries shall be made at receiving end in this register in addition to TSR []
 A) T / A 1425 B) T / B 1425 C) T / 1525 D) All the above
363. While issuing PLCT, Loco Pilot's signature is to be obtained in []
 A) column A of T / A 1425 B) column A of T / B 1425
 C) column B of T/A 1425 D) column B of T / B 1425
364. Accidents are classified into how many categories []
 [A] One B] Two C] Three D] Five
365. An example of consequential accident is []
 A] Signal passing at "ON" B] Entering into B/S w/o ATP C] Fire on train D] Averted collision
366. An example of indicative accident is []
 A] Breach of block rules B] Fire on train C] Collisions D] LC gate accidents
367. Passing stop signal at Danger is this type of accident []
 A] Indicative accident B] Averted accident C] consequential train accident D]
 none of above
368. On trunk routes when traffic is disrupted for following hours or more, it is treated as serious dislocation of traffic. []
 A] 12 hours B] 3 hours C] 24 hours D] 6 hours
369. To treat any accident as averted collision, outside station limits, the distance between two trains shall be []
 A] 600 meters or less B] less than 400 meters C] 1400 meters or less D] 180 meters or less
370. When a person is knocked down or run over and dead, no responsible person is available, body shall be []

A] a month B] 2 months C] 3 months D] a year

385. This is considered as dangerous for running trains (Rainfall in 24 hours) []
A] 1 cm B] 5 cm C] 10 cm D] 15 cm
386. Heavy wind is considered dangerous for running trains if wind velocity is []
A] 60 kmph or more B] 65 kmph or more C] 50 kmph or more D] 5 cms or more
387. For the purpose of Weather Warning, South Central Railway is divided into []
A] 5 zones B] 6 zones C] 7 zones D] 4 zones
388. Ex- gratia to be paid In case of death in Train/ manned Level Crossing accident is Rs []
A] 6,000 B] 10,000 C] 25,000 D] 50,000
389. Ex-gratia to be paid in case of serious injury in a Train/manned LC gate accident is Rs. []
A] 25,00 B] 10,000 C] 25,000 D] 50,000
390. Ex-gratia to be paid in case of simple injury in a Train/manned LC gate accident is Rs. []
A] 5,000 B] 10,000 C] 25,000 D] Nil
391. The claim for compensation shall be made within the following time from the date of accident []
A] 1 year B] 2 year C] 6 months D] 3 years
392. The claim for compensation shall be made through []
A] Railways Claims Tribunal B] Civil court C] High court D] District court
393. General Rules are framed by []
[A] Railway Board [B] Authorised Officer [C] General Manager [D] PCOM
394. Approved special instructions are issued or approved by []
[A] PCOM [B] Authorised Officer [C] CRS [D] Railway Board
395. A fixed stop signal of a station controlling the entry of trains into next block section is []
[A] FSS [B] LSS [C] Outer [D] Home
396. This includes a train, vehicle or obstacle on or fouling a line, or any condition which is dangerous to trains []
[A] shunting [B] connection [C] communication [D] Obstruction
397. Special instructions are issued by []
[A] CTM [B] CSO [C] Authorised Officer [D] Railway Board
398. At a Block station the Station Limits are between []
[A] two outermost signals [B] two outer signals [C] two FSS [D] Two LSS
399. On Double line class 'B' station Multiple Aspect Signalling, station section lies between []
(A) outermost facing points to LSS (B) BSLB to LSS (C) Either A or B (D) none of above

400. On single line 'B' class MAS station, Station section lies between []
 (A) Two Advance Starters (B) Two SLBs (C) Two outer most points (D) any one of the above
401. The system adopted for the time being for the working of trains on any portion of a railway is Known as []
 [A] system of controlling [B] Direction of traffic [C] System of working [D] None of these
402. No Railway Servant directly connected with the working of trains shall take or use any alcoholic drink, sedative, narcotic or stimulant drug or preparation before the commencement of his duty within []
 [A] 6 hours [B] 8 hours [C] 10 hours [D] 12 hours
403. Whenever two yellow lights are exhibited in Distant signal the Aspect is []
 [A] Caution [B] Attention [C] Stop [D] Proceed
404. Whenever one yellow light is exhibited in Distant signal the Aspect is []
 [A] caution [B] attention [C] proceed slow [D] proceed
405. The indication of the Distant signal in Caution Aspect is []
 (A) Stop dead
 (B) Proceed and be prepared to stop at the next stop signal
 (C) Proceed and be prepared to pass the next stop signal at a restrictive speed
 (D) proceed
406. In Double distant area, The indication of the Distant signal in Attention Aspect is []
 (A) Stop dead
 (B) Proceed and be prepared to stop at the next stop signal
 (C) proceed and be prepared to pass the signal at a restrictive speed
 (D) B or C
407. In single distant area, if Distant signal is showing proceed aspect, it means []
 (A) Stop dead
 (B) Train is admitted on to loop line
 (C) train is run through via main line, block section ahead is free
 (D) Train is admitted on to main line, to stop at station
408. In single distant area, If distant signal is showing attention aspect it means []
 (A) Train is admitted on to loop line
 (B) train is run through via loop line, block section ahead is free
 (C) Train is admitted on to main line to stop at starter (D) Any of the above
409. The signal which tells about the aspect of stop signal ahead is []
 (A) outer (B) Distant (C) advance starter (D) none of these
410. The normal aspect of Distant signal on double distant signal area is []
 [A] Caution [B] Attention [C] Stop [D] Proceed
411. When colour light Distant signal is combined with Gate/LSS, normal aspect of that signal is []

[A] Stop [B] Caution [C] Attention [D] Proceed

412. The light that is displayed when colour light Calling On signal is taken 'OFF' []
 (A) miniature yellow (B) miniature red (C) green (D) yellow
413. The indication of the Calling On signal when taken 'OFF' is []
 (A) proceed and be prepared to stop at next stop signal
 (B) Be prepared to stop short of any obstruction
 (C) stop dead
 (D) proceed cautiously
414. The occasions when Calling ON signal can be used are []
 A) receiving a train on obstructed line B) when signal above is defective
 C) either A or B D) none of the above
415. To take "OFF" calling ON signal, the train must come to a stop on []
 A) Axle counter B) free zone C) calling on zone D) distant signal
416. Shunt signal below stop signal, in 'ON' position will show []
 [A] red light [B] two white lights horizontally [C] no light [D] yellow light
417. The Aspect of independent shunt signal at 'ON' is []
 [A] Stop [B] Caution [C] Attention [D] No light
418. The color lights exhibited in Position light shunt signal in 'OFF' position is []
 A) two white lights horizontally B) two white lights diagonally
 C) two green lights D) two yellow lights
419. The authority to pass defective Independent shunt signal or shunt signal below stop signal at "ON".
 Is []
 A) T.369(1) B) T.806 C) PLCT D) T.369(3b)+PHS
420. When a fixed signal is not in use, it shall be distinguished by []
 A) two crossed bars B) two parallel bars C) two horizontal bars D) one vertical bar
421. Route indicators are treated as []
 A) permissive signals B) stop signals C) subsidiary signals D) Duplicate signals
422. When a signal is newly erected or shifted, caution order shall be given for a period of []
 A) 20 days B) 10 days C) 90 days D) 60 days
423. When a signal newly erected or shifted, in addition to issuing of caution order, it shall be notified in []
 A) SOB B) Station Diary C) TSR D) Sign 'ON' register
424. The marker board by which Gate signal is identified by []
 A) 'IB' B) 'P' C) 'G' D) 'A'
425. The marker board for indicating the Outlying siding points are []

[A] 'A' [B] 'IB' [C] 'S' [D] 'G'

426. The speed of a goods train while entering terminal yard is restricted to []
[A] 8kmph [B] 10kmph [C] 15kmph [D] 20kmph
427. A signal which is taken "OFF" for a train will be put to "ON" position in emergency only to []
A) obey SCOR instructions B) obey advance SM instructions
C) issue tickets D) avert an accident
428. After putting back starter/advanced starter for departing train LP of the train should be advised by
A) written memo B) C.O. C) T.369 (3b) D) none of above
429. The aspect in the normal position of fixed signals except Automatic Signals is []
[A] Attention [B] caution [C] proceed [D] most restrictive aspect
430. Even though departure signals are taken off, LP shall stop at stations where stoppages are scheduled in the []
[A] VG [B] CTR [C] WTT [D] SOB
431. The signals that are prohibited to be used for shunting purposes is/are []
A) Outer B) Home C) LSS D) All the above
432. Slip siding is intended to protect []
[A] Outlying siding [B] Block section [C] station section [D] station limits
433. Catch siding is intended to protect []
[A] Outlying siding [B] Block section [C] station section/station [D] station limits
434. By waving green flag by day and a white light by night up and down vertically as high and as low as possible indicate []
A) move slowly B) move towards person signaling C) train parting D) coupling
435. Violently waving a white light horizontally across the body of a person indicates []
[A] train parting [B] move away from the person showing [C] proceed [D] stop dead
436. Detonators are also known as []
[A] fog signals [B] flare signals [C] illuminating signal
[D] none of these
437. Normal life of a detonator manufactured during 2010 and afterwards is []
[A] 3 years [B] 5 years [C] 7 years [D] 10 years
438. The maximum number of extensions after successful testing of the detonator is []
[A] one [B] two [C] three [D] any number
439. The signals to be used to warn the incoming train of LP about an obstruction at night shall be a []
A) flashing amber light B) red flag C) Red flashing H/S lamp D) none of these

440. A blank signal under complete power off situation is to be treated as []
 A) Defective signal B) Signal at off C) no signal D) none of above
441. When home is defective and pre warning is given, the LP may pass such signal on receipt of []
 [A] PHS at the foot of the defective signal [B] PHS at the first facing points
 [C] T.369(3b)+PHS [D] PN through SPT
442. Advance authority to pass defective signal is []
 [A] T.369 (3b) [B] T.369 (1) [C] T/C.1425 [D] T.409
443. Authority to pass defective starter signal (if it is not LSS) is []
 (A) T.369(3b)+ PHS B) calling on signal taken off C) either A or B (D). PLCT
444. On Double line /Single line token less section when LSS is defective Authority to proceed is []
 [A] T.369 (3b) [B] PLCT [C] T.806+PN [D] T/C.602
445. The authority required by Loco Pilot when passes starter at "ON" partly and stopped before Advanced Starter, []
 A) memo countersigned by Guard B) T.369(3b)+PHS C) ATPD) all the above
446. During day when Gate signal is at ON, the LP shall wait for []
 A) one minute B)two minute C)three minute D)four minute
447. When Gate signal is at ON, the LP shall wait one/two minutes by day/night and gateman not available, LP may pass the gate after ensuring it is closed on the hand signals of []
 A) Gangman B) train crew C) patrolman D)PWI
448. During night when Gate signal is at ON, the LP shall wait for []
 A)one minute B)two minutes C)three minutes D)four minutes
449. When Gate signal is at ON, the LP shall wait one/two minutes by day/night and gateman exhibiting hand signals. LP may []
 A) stop at the gate B) proceed at MPS C) proceed cautiously D) none of above
450. If a signal is showing white light in place of a colour light, it is treated as signal is showing []
 A) most restrictive aspect B) caution aspect C) attention aspect D) Proceed aspect
451. The signal shall be treated as defective, whenever colour light signal is flickering / bobbing and does not assume a steady aspect at least for []
 [A] 20 sec [B] 30 sec [C] 60 sec [D] 120 sec
452. The authority given to the loco pilot at station when I B S is defective []
 A) PLCT B) T.369 (3b) C) Both A & B D) none of above
453. When I B S is at "ON" immediately the Loco Pilot shall stop and contact []
 A) SM of advance station B) SCOR C) SM in rear station D) TPC
454. When IBS is at "ON" and the telephone is out of order, Loco Pilot shall wait for []

A) two minutes B) three minutes C) four minutes D) five minutes

455. When IBS is at "ON" and the telephone is out of order, Loco Pilot after waiting for five minutes shall proceed when view is clear/not clear upto FSS of next station speed of []
 A) 10/8kmph B) 25/10kmph C) 20/10kmph D)15/8kmph
456. Over the traileed through points, under no circumstances should a train be []
 [A] move forward [B] backed [C] run with MPS [D] none of these
457. The Loco Pilot shall whistle intermittently when his engine explodes detonator and take every possible caution as necessary including []
 A) increase of speed B) stop the train C) proceed with MPS D) reduction of speed
458. After exploding the detonator, if no obstruction found further, the Loco Pilot, can pick up normal speed after proceeding cautiously up to a distance of []
 [A] 500 meters [B] one KM [C] 1.5 KM [D] 2 KM
459. When the Loco Pilot notices a signal warning of an obstruction, except detonator, he shall []
 [A] proceed cautiously [B] proceed upto next station and report
 [C] stop after noticing the obstruction [D]stop immediately
460. When the Loco Pilot notices a signal warning of an obstruction and no further details are noticed, shall stop during day/night for []
 A) one/two minute B) two/three minutes C) 3/4 minutes D) none of these
461. When the Loco Pilot notices a signal warning of an obstruction and no further details are noticed, after stopping one/ two by day/night, he shall proceed upto the next block station []
 A) cautiously B) with MPS C) at 20kmph D)at 30 kmph
462. In rear of FSS, the Signal warning board is located at a distance of []
 [A] 180 meters [B] 400 meters [C] 1000 meters[D]1400 meters
463. The Loco Pilot and guard will be given three no. of L R trips before they are booked for regular working including one trip between []
 A) sunset to sunrise. B) 06.00hrs to 20.00hrs.
 C) 21.00hrs to 07.00hrs D) 20.00hrs to 06.00hrs
464. Guard shall set his watch by the station clock or the clock at the authorized place of reporting for duty and communicate the time to the LP and make entry in the []
 A) memo book B) CTR C) TSR D) defective register
465. ODC shall be allowed to be attached by a train for transport only with the prior sanction of []
 [A] CRS [B] RAILWAY BOARD [C] TXR [D] PCOM
466. The Guard shall not give the signal unless he satisfies that no person is travelling []
 [A] in any vehicle or compartment for not use of passengers [B] roof of the vehicle
 [C] A and B [D] none of the above

467. Even under normal circumstances subject to observance of permanent / temporary speed restrictions in force all Passenger carrying trains should run at []
A) booked speed. B) maximum permissible speed C) 110kmph D) 100kmph
468. How many times time table will be changed in railways in a year. []
A) 1 B) 2 C) 3 D) Non of the above
469. During dense fog maximum speed of a train on Absolute block system shall be restricted to (loco fitted with fog signal device)[]
A) 30kmph B) 50kmph C) 75kmph D) 20kmph
470. Normally the speed of trains over Non-Interlocked points, turnouts and crossover shall not exceed []
[A] 8 kmph [B] 10 KMPH [C] 15 KMPH [D] 30 KMPH
471. The speed of a passenger/goods train on 1 in 8 ½ turnout (thick web switch, symmetrical layout of 52/60 km rails) on PSC sleepers is restricted to []
[A] 8 kmph [B] 10 KMPH [C] 15 KMPH [D] 30 KMPH
472. Engine pushing is not permitted without the prior permission of []
A) SM of advance station B) SM of rear station
C) SM of the notice station D) none of above
473. When engine is pushing a train and Guard is travelling in brake van, which is leading, the speed shall not exceed []
A) 25kmph B) 10kmph C) 8kmph D) walking speed
474. When engine is pushing a train and Guard is not travelling in leading vehicle, the speed shall not exceed []
A) 25kmph B) 10kmph C) 8kmph D) walking speed
475. When the train is working without BV, while pushing back the LP has to observe the hand signals of guard and proceed with []
A) 25kmph B) 10kmph C) 8kmph D) walking speed
476. When head light is defective after putting marker lights 'on' train can go with a restricted speed of []
A) 40kmph B) severest speed of the section
C) A or B whichever is less D) none of above
477. Last vehicle indicator during night shall be []
A) L.V board of approved design [B] retro reflective L.V board
C) red flashing light [D] red flag
478. Side lights shall show towards engine in normal position []
A) red light B) white light C) green light D) yellow light
479. Side lights shall show towards rear in normal position []
A) Red B) white C) green D) yellow

480. At night, when passenger carrying train waiting at a station for precedence, Guard shall change the side light adjacent to the line on which the following train is to be admitted, to show light towards rear is []
A) Red B) white C) green D) yellow
481. At night, when passenger carrying train waiting at a station for precedence, Guard shall change the side light adjacent to the line on which the following train is to be admitted, to show light towards engine is []
A) Red B) white C) green D) yellow
482. What shall be fixed behind an assisting engine when it is attached in rear of a train? []
A) tail board B) Tail lamp C) either 'A' or 'B' D) red marker lights.
483. It will be the duty of the Guard to ensure the last vehicle only in rear is affixed with []
A) Tail lamp B) tail board C) red flag D) tail board/tail lamp
484. In case of obstruction on track, during day Guard must exhibit []
A) red flag B) flashing red light C) steady red light D) amber light
485. In case of obstruction on track, during night Guard must exhibit hand signal lamp showing []
A) red flag B) flashing red light C) steady red light D) amber light
486. Whenever alarm chain is pulled the Guard shall record the fact in the []
A) TSR B) Station diary C) memo book D) CTR
487. Whenever alarm chain is pulled, Guard shall record the fact in CTR and submit a special report to []
A) DOM B) DME C) DRM D) DSC
488. Guard shall report to the Station Master of the next important station, any stoppage or other irregularities in train working and record the details in []
A) TSR B) Station diary C) memo book D) CTR
489. The full form of OTL of BV equipment is []
A) over time leave B) one time lock C) one time leak D) one time lever
490. SM/TNC of the originating station shall record the intactness and availability of the BV equipment in the register and obtain acknowledgement of []
[A] Guard [B] S.E (C&W) [C] LP when without guard [D] none of the above
491. At destination station, Guard shall obtain acknowledgement about the intactness of OTL and seal of Dy.SS or SE / JE-C&W in the []
[A] Rough journal/VG [B] CTR [C] LTM [D] RS-5
492. The number of persons permitted to travel in the brake-van of goods trains, in addition to the Guard, should not exceed []
[A] 2 [B] 3 [C] 5 [D] 6

493. In emergency a goods train without brake van is ordered by []
 A) DOM B) Sr.DOM C) either A or B D) DRM
494. Maximum number of coaches in addition to the officers inspection coach attached in rear of SLR of Passenger & Mail / Express trains is []
 [A] 2 [B] 3 [C] 5 [D] 1
495. Maximum number of bogies or its equivalent attached in rear of rear brake van by a goods train is []
 [A] 2 [B] 3 [C] 5 [D] 1
496. Maximum number of damaged vehicle or damaged engine shall be attached behind the rear brake van of goods/mixed train []
 [A] 2 [B] 3 [C] any number if certified by SSE(C & W/LOCO) [D] 1
497. Attaching of damaged vehicle/engine may done during []
 [A] day time B) clear weather C) Both A & B D) any time
498. All irregularities in connection with the working of trains must be reported by Guard in the []
 [A] VG [B] CTR [C] LTM [D] RS-5
499. Whenever vehicles are attached/detached to a train at intermediate stations, the entries in the VG must be made by the []
 A) Guard B) Station staff C) Loco Pilot D) none of these
500. Before starting, the guard will be responsible for checking the load on the train check and tally wagon numbers, booking and destination stations, type of wagons etc., with the entries on the []
 [A] VG [B] CTR [C] LTM [D] RS-6
501. Trucks loaded with girders, machinery, long timber etc. shall be inspected by Guard at stopping stations and they shall be re-secured if the []
 A) fastenings have slackened B) loads shifted
 C) either A or B D) none of these
502. At stations, where PA system is not provided, SM gives permission to Guard to stat the train by ringing beats for Up/Dn trains is []
 A) two/three B) three/two C) three/four D) four/three
503. The Loco pilot /ALP & Guards must look back at the Gang Staff & Level Crossing Gates to see whether any []
 [A] Stop hand signal is exhibited [B] proceed hand signal is exhibited
 [C] need not see [D] none of these
504. The following are exempted from exchanging 'All right' signals []
 [A] LP/Motormen of DMUs, EMUs [B] LP of a train W/O guard
 [C] Guards of A/C SLRs [D] none of these
505. The Guard shall protect in rear when a train is held up at F S S for more than []
 A) 5minutes B) 10minutes C) 15minutes D) 20minutes

506. If Guard failed to attract the attention of LP , when notices any danger condition in the train, he may stop the train gradually by applying []
 A) vacuum/air pressure brake B) dynamic brake C) loco brake D) loco hand brake
507. The number of hand brakes of vehicles that must be applied whenever the engine is to be detached outside station limits when the gradient is not steeper than 1 in 600 is []
 A) BV+6 B) BV+12 C) BV+18 D) BV + all
508. The number of hand brakes of vehicles that must be applied whenever the engine is to be detached out side station limits when the gradient is steeper than 1 in 600 is []
 A) BV+6 B) BV+12 C) BV+18 D) BV + all
509. When working a passenger train the Loco Pilot shall ensure that the passenger bogies do not over shoot the []
 A) platforms [B] starter [C] shunt signal if any [D] none of these
510. Whenever a train is stopped on a gradient for any reason like accident, loco failure, OHE supply failures etc., it is essential and important to apply the []
 A) A9 [B] SA9 [C] Both A & B [D] none of these
511. The whistle code, that is given by the Loco Pilot when SM / Station Staff does not exchange ' all-right' signals is[]
 A) 00 [B] 000 [C] 00 _ [D] 00 _,_
512. When engine whistle fails on run, after clearing block section cautiously and []
 [A] continue with 40 kmph [B] Advise PCOR/TLC and act accordingly
 [C] ask for repair or relief [D] none of these
513. Engine Whistle code for Guard to Protect train in rear is []
 A) 00 B) 000 C) 0000 D) -- --
514. Engine Whistle for Guard to come to Engine is[]
 A) 00 B) 000 C) 0000 D) _ ,_00
515. Whistle code while Passing Signal at 'ON' with proper Authority []
 A) 0-0 B) 00- C) 0 D) 00
516. Engine whistle code 0 0 - indicates []
 A) Defective signal B) alarm chain pulled
 C) guard to come to engine D) passing signal at On with proper authority
517. The Bell Code used in EMU/DMU for Zone of Speed restriction is over and to resume normal speed is []
 A) 0 pause 0 B) 00pause 00 C) 000pause000 D) 000000

518. Whenever train stopped without clearing fouling mark, to prevent any movement on the fouled line the Guard shall inform the SM at once by []
 A) showing green flag B) waving white light C) exchange of PN D) exhibiting stop hand signal
519. To dispatch a material train for working in the block section and return back to the same station, authority given to the LP []
 A) PLCT [B] ATP W/O line clear [C] T/462 [D] T/A.462
520. The authority given to the LP to dispatch a material train for working in the block section and proceed to the next station []
 A) T.462 [B] T/A.462 [C] T.465 [D] none of these
521. The validity of material train B P C is []
 A) 30 days [B] 21 days [C] 15 days [D] none of these
522. While stabling a material train at a station, the responsibility to secure it lies with the []
 A) Guard [B] Station Master [C] SM & Guard [D] Guard and PWI
523. Written authority for Loco Pilot to receive a train on to an obstructed line []
 A) T/511 [B] pilot in memo [C] T/369(3b) [D] T/509
524. While receiving a train on an obstructed line, STOP hand signal shall be exhibited from the point of obstruction at a distance of not less than []
 [A] 45 meters [B] 20 meters [C] 120 metres [D] 180 metres
525. Written authority for Loco Pilot to receive a train on to non signalled line []
 A) T/511 [B] pilot in memo [C] T/369(3b) [D] T/509
526. Written permission to start a train from a station having common starter,[]
 A) T/511 [B] pilot out memo [C] T/512 [D] T/509
527. To dispatch a train from non-signaled line, where tangible authority is not given as A T P, authority to be given in addition to ATP[]
 A) T/511 [B] pilot out [C] T/512 [D] T/509
528. As per G & S R signals used for controlling shunting operations shall be []
 A) Fixed signals or hand signals or verbal orders [B] fixed and hand only
 C) Fixed signals only [D] none of these
529. The speed during shunting operations shall not exceed []
 A) 10 kmph [B] 15kmph [C] 30 kmph [D] 8 kmph
530. Except in case of doubt the shunting staff need not accompany during shunt movement of light engine/s on to a []
 A) Siding [B] LP in leading cab [C] attaching to formation [D] Free line
531. Slip coaches shall not be kept on blocked line in the rear of a []
 A) passenger train [B] light engine [C] shunting engine [D] stabled load

532. While performing shunting on passenger carrying trains, the shunting engine or train engine, before coming on to the formation should be stopped before the formation at a distance of []
 A] 45 meters [B] 20 meters [C] 15 meters [D] 10 meters
533. At station where separate shunting staff are not employed, shunting operations shall be personally supervised by []
 A] points man [B] Loco pilot [C] SM [D] Guard
534. While backing a full train from one line to another via main line, shunting supervision is done by []
 A] points man [B] Loco pilot [C] SM [D] Guard
535. Carriages containing passengers shall not be moved for shunting purpose without the personal orders of the []
 A] SM & LP [B] GD & SM [C] GD [D] GD & LP
536. While performing shunting, the points which are not protected by signals must be locked by following methods []
 A] clamped and padlocked [B] cotter bolted and padlocked
 [C] Either A or B [D] none of these
537. While shunting wagons containing explosives, the supervision shall be done by []
 A] points man [B] Loco pilot [C] SM [D] Guard
538. The maximum speed while shunting of wagons containing explosives and P O L products shall be []
 A] 10 kmph [B] 15 kmph [C] 30 kmph [D] 8 kmph
539. The gradient that is considered as steep gradient for the purpose shunting of roller bearing wagons [A]. 1 in 400 [B]. 1 in 600 [C]. 1 in 260 [D]. 1 in 150
540. Shunting of roller bearing vehicle on a steep gradient shall be done only with locomotive attached towards the
 [A] As per convenience [B] falling gradient [C] Raising gradient [D] one of these
541. When Loco Pilot of the train experienced any abnormal condition in the track, In case of IBS and automatic block territories, the LP must inform through available means. []
 [A] Station Master [B] Loco pilot of trains already left [C] Both A and B [D] None of these
542. While stabling goods train having BOX 'N' / BCN / BRH, etc., minimum no. of vehicles hand brake to be applied from in addition to hand brakes of B/V are []
 [A] 3 effective wagons from each end [B] six effective wagons from each end
 [C] nine effective wagons from each end [D] 10 from engine 5 from B/V
543. When Loco Pilot of the train experienced any abnormal condition in the track, shall stop his train at
 [A] LSS of next station [B] Home of next station
 [C] within station section [D] next block station without clearing block section
544. When 'lurch' is reported and subsequently a train is sent in the absence of engineering official, caution order is given to the LP to stop dead if considered safe, proceed at a speed of []

- A] 10 kmph [B] 15 kmph [C] 30 kmph [D] 8 kmph
545. Rail fracture of less than 30mm, the speed of first train shall be []
[A] 10 kmph [B] 15kmph [C] 30 kmph [D] 8 kmph
546. Rail fracture of less than 30mm, the speed of second and subsequent trains shall be []
[A] 10 kmph [B] 15kmph [C] 30 kmph [D] 8 kmph
547. Rail fracture of more than 30 mm or multiple fractures, to pass trains track is to be certified by []
A] AEN [B] PWI [C]key man [D] Gang mate
548. During Temporary Single Line working, Authority given to Loco Pilot[]
[A] PLCT [B] CLCT [C] T/D.602 [D] T/369(3b)
549. During Temporary Single Line working, the speed of first train shall be[]
[A] 25 kmph [B] 10 kmph [C] 15 kmph [D] MPS
550. During Temporary Single Line working when the train is proceeding on wrong line, in addition ATP, the train shall be dispatched by issuing[]
[A] pilot out memo [B] T/369(3b) [C] T/511 [D] T/512
551. During Total Interruption of Communication on double line authority to the Loco Pilot is []
[A] T/C.602 [B] PLCT [C] T/B.802 [D] CLCT
552. During Total Interruption of Communication on double line, the Loco Pilot to proceed with a restricted speed of []
[A] 25/10 kmph [B] 15/8 kmph [C] 20/10 kmph [D] 15/10 kmph
553. Authority for light engine/vehicle which is going to open communications is []
[A] T/A.602 [B] T/B.602 [C] T/C.602 [D] T/D.602
554. If it is required to dispatch a relief engine or relief train into obstructed block section, it can be dispatched by issuing []
[A] T/A.602 [B] T/B.602 [C] T/C.602 [D] T/D.602
555. On Double line, Protection on same line in front is required when []
[A] accident occurred [B] relief engine is asked
[C] train stopped for 15 mins [D] none of these
556. If the stoppage happened (more than 15 minutes) on a grade steeper than 1 in 150 for roller bearing stock(goods train), the number of hand brakes to be applied in addition to the application of brake van hand brake.[]
[A] 6 wagons from each end [B] 6 from each end and 6 in centre
[C] 10 inside engine+5 inside B/V or one third whichever is more [D] all wagons
557. When engine disabled, LP will request the Guard to arrange for a relief engine if the LP expects that putting the engine in working order will take more than []
[A] 5 minutes [B] 10 minutes [C] 20 minutes [D] 30 minutes

558. When a train parts on its journey, the tonnage of the train shall be jointly checked by[]
 [A] SM&GD [B] GD&LP [C] SM,GD&TXR [D] SM,GD & LP
559. If Loco Pilot enters block section without authority and subsequently sends his Assistant Loco Pilot with a memo to SM in advance, that S M shall give[]
 [A] PLCT [B] Caution order [C] T/A.602 [D] T/369(3b)
560. During divided train working, the Guard will prepare a written permission give to Loco Pilot to proceed to the next station in the form[]
 [A] T/A.602 [B] Caution order [C] T/609 [D] Written memo
561. At night, during divided train working, the second portion of the train left in section shall be protected in the rear by[]
 [A] Guard [B] ALP [C] both ALP and guard [D] none of these
562. The light engine which is coming on T/609 to pick up the second portion shall come with a restricted speed of[]
 [A] 25kmph [B] 15/10 Kmph [C] normal speed [D] 15/8 Kmph
563. In case of fire accident in a passenger carrying train, the first objective to be achieved is to[]
 [A] Safety of passengers [B] Extinguish fire
 [C] isolate fire coach [D] Switch off power supply
564. In the event of a fire on any part of the electrical equipment, the affected part is first to be completely[]
 [A] isolated from power supply [B] put off fire [C] First 'A' and then 'B' [D] none of these
565. The following shall not be used for extinguishing fires on electrical equipment.
 [A] dry chemical powder [B] sand [C] water [D] none of these
566. On D/L the automatic signal shall not assume OFF position unless the line is clear not only upto the next Automatic signal but also for an adequate distance of not less than[]
 [A] 180 meters [B] 120 meters [C] 400 meters [D] 100 meters
567. All Guards, Loco Pilots, Assistant Loco Pilots, Motor men who are required to work in automatic block system shall undergo one day intensive training and a certificate shall be renewed once in []
 [A] 3 months [B] 3 years [C] 5 years [D] 6 months
568. SMR/TI shall renew the competency certificates (Automatic section) for []
 [A] SMs [B] Guards of that station [C] SMs and points men [D] none of these
569. When Loco Pilot passes an automatic signal at ON, he shall observe SR of[]
 [A] 8 kmph [B] 10kmph [C] 15 kmph [D] 25 kmph
570. When the train has been stopped at an Automatic stop signal, the signal that guard shall show towards the rear[]

[A] Stop [B] Signal warning of obstruction ahead [C] amber flasher light [D] Proceed

571. After passing an automatic signal at ON, the Loco Pilot of the following train hauled by any locomotive shall ensure that a minimum distance to be maintained between his train and preceding train is
 [A] 120 meters [B] three OHE masts
 [C] 150 meters or two OHE masts [D] none of these[]
572. When LSS fails on single line automatic block system, Authority to proceed to Loco Pilot is []
 [A] PLCT, [B] PLCT+T/A.912 [C] CO+T/A.912 [D] T/369(3b) +C.O OF 10 KMPH
573. When LSS fails on double line automatic block system, authorities to be given to LP of the train
 [A] PLCT+ C.O of 10 kmph [B] PLCT+T/A.912
 [C] T/D.912+T/A.912 [D] T/369(3b)+ C.O of 10 kmph
574. When a train is stopped in an automatic block signaling section on single line and train cannot proceed further, the Guard shall protect in rear duly placing detonators at[]
 [A] 250M, 500M, &510M [B] 90M, 180M, &190M
 [C] 600M, 1200M, 1210M [D] 90M,180M,190M &200M
575. During prolonged failure of signals but communications are available on D/L Automatic Block System, the authority given to Loco Pilot is.[]
 [A] T/ D 602 [B]T/ D 912 [C]T /C 602 [D] T /B 912
576. When signals and communication fail on Double line Automatic Block System, the authority given to the Loco Pilot is[]
 [A] T/ B 602 [B]T/ D 912 [C]T /C 602 [D] T /B 912
577. In the automatic block system, to dispatch a relief loco/train into the occupied block section authority given as the ATP for the relief loco/ train[]
 [A] T/B.602 [B]T/ C 912 [C]T /D 602 [D] T /B 912
578. Relief loco/train shall proceed with a restricted speed of[]
 [A] 25kmph [B] 15/10 Kmph [C] normal speed [D] 15/8 kmph
579. When Gate signal in Automatic signaling territory is at 'ON' and 'A' marker is not illuminated, LP shall follow the rules of passing[]
 [A] gate rules [B] gate rules and automatic rules
 [C] automatic rule only [D] none of these
580. LP shall pass a Semi Automatic signal with extinguished .A' marker at 'ON' on receipt of written authority[]
 [A] T/369(3b) [B] T/A.912 [C] T/D.912 [D] T/C.912
581. The normal authority to proceed on Single Line token less sections/Double line sections []
 [A] 'OFF' position of LSS [B] PLCT
 [C] PLCT or token [D] Any written document signed by SM

582. At stations where BPAC is not provided, the Guard of the train, after verifying the last vehicle is standing clear of the fouling mark, inform Station Master by []
 [A] waving arm by day [B] P.N exchange through walkie-talkie
 [C] showing white light by night [D] none of these
583. Occasions where exchange of private numbers between SM and guard is not required for ensuring complete arrival of train []
 [A] clear indication of BPAC [B] run through trains
 [C] end cabins are provided [D] All the above
584. During line block, to receive the units coming on right line, authority to receive the first unit []
 [A] taking 'off' signals [B] pilot in memo [C] T/509 [D] none of these
585. During line/integrated/shadow block, if the units are coming on wrong line, units shall be received on []
 A] taking 'off' signals [B] pilot in memo [C] T/509 [D] none of these
586. From the obstruction (work spot), Engg. Stop indicator is located at []
 [A] 45 meters [B] 1200 meters [C] 400 meters [D] 30 meters
587. From the obstruction (work spot) Engg. Speed indicator is located at []
 [A] 45 meters [B] 1200 metres [C] 400 metres [D] 30 metres
588. On BG from obstruction (workspot) Engg. Caution indicator is located at []
 [A] 45 metres [B] 1200 metres [C] 400 meters [D] 30 metres
589. After stopping at the stop indicator, Loco Pilot shall sign in this book and proceed with restricted speed of []
 [A] ER-7, 10 KMPH [B] ER-7, 8 KMPH [C] RS-6, 8 Kmph [D] rough journal, 10 KMPH
590. When major work such as relaying and re-girding is in progress a speed restriction that shall be observed on the adjoining line of DL//MULTIPLE/ line section []
 [A] 45 kmph [B] 50 kmph [C] stop dead and proceed [D] 30 kmph
591. When water rises above the ballast level but below rail level, train should be allowed as per following
 [A] a train shall not be allowed
 [B] a train must stop and proceed after the velocity of the water is reduced
 [C] train must stop and be piloted by the PWI.
 [D] track should be walked over by two men abreast one at either end of the sleepers before the train
592. When water overflows above the rails - []
 [A] a train shall not be allowed
 [B] Train must stop and proceed after the velocity of the water is reduced.
 [C] train must stop and be piloted by the PWI.
 [D] train must stop and be piloted by gang man

593. Neutral section lies between two consecutive []
 [A] section insulators [B] block stations [C] sub stations [D] OHE depots
594. Danger Zone" means the zone lying around any live equipment within radius of []
 [A] 45 meters [B] 2 meters [C] 2.5 meters [D] 30 meters
595. When a train comes to a stop in an electrified section and the cause of stoppage is not immediately obvious, The LP and GUARD shall immediately take an action []
 A) Protect train B) Ask relief Engine C) Protect train after engine only D) None of these
596. The speed of the train while passing through Neutral section shall not be less than []
 [A] 45 kmph [B] 20 kmph [C] 40 kmph [D] 30 kmph
597. When the tower wagon is moved, attached to a train, it should be inside the []
 [A] engine [B] working engine [C] rear B/V [D] Sixth vehicle
598. When the tower wagon is attached to a train, the speed of the train should be []
 [A] MPS of train [B] Speed stenciled on tower wagon
 [C] as per load of the train [D] Sectional speed
599. When healthy section is temporarily isolated and re-energised, if train entered faulty section, the speed of the first train by day / night shall be
 [A] 25/10 kmph [B] 20/10 kmph [C] 40/40 kmph [D] 60/30 kmph
600. The permission, The GUARD of the train with the ODC receives from the authorized person, to enter the section(Electrified) is []
 A) Permission from CHC B) Permission from TPC
 C) Tralley/ Lorry notice D) permit to work
601. The notice stations, where divisional caution order shall be issued are specified in the []
 [A] Working time table [B] rake link [C] CTR [D] Gradient chart
602. In the Caution order, the names of the stations concerned should be written in full, and this should not be used
 [A] letters [B] Codes [C] Capitals [D] Numerals
603. The caution order should have all the speed restrictions in force in []
 [A] geological order [B] gradient wise [C] Geographical order [D] control section wise
604. The LP shall not start the train/the Guard shall not give signal to start from a notice station until they have received []
 [A] Divisional CO [B] PSR [C] TSR [D] Memo
605. In case of change of train crew en route, the Guard taking over charge must take over all Caution Orders from []
 [A] In coming crew [B] SM of that station
 [C] TTE of the train [D] from loco pilot of assisting engine if any

606. During passage of trains, the position of Gateman during day time and during night time[]
 [A] holding unfurled flags/green light [B] holding furled red and green flags/white light
 [C] green flag/green light [D] holding unfurled green flag/no light
607. A common NI home signal without route indicator should be provided for any indirect reception of trains, with []
 [A] stop& caution aspect [B] stop& proceed aspect
 [C] Proceed with caution aspect [D] No aspect at all
608. During non interlocking working, All trains must be brought to a stop at the FSS and then allowed to enter (taking off signals) cautiously at speed not exceeding
 [A] As per standard of interlocking [B] 20 kmph [C] 15 kmph [D] 30 kmph
609. During NI working, the LP shall not pass the outermost facing points even though signals are taken off unless he also receives.
 [A] caution order at points [B] PHS at points [C] T/369(3b) [D] none of these
610. During NI working the ASM/Guard/SWM in charge of the goomties shall be responsible for[]
 [A] exchanging PHS at outermost facing point
 [B] correct setting, clamping and pad locking of points
 [C] Exchanging P.N with SM for each train
 [D] All the above
611. Patrolling of line means in addition to the daily inspection carried out by key man of the gang
 [A] Inspection of L.C. Gates [B] Inspection of line by foot
 [C] Surprise night inspection [D] all the above
612. Patrolling of railway line is done on following occasions.[]
 [A] Security patrolling during civil disorders
 [B] Watch at vulnerable points during monsoons
 [C] Monsoon patrolling
 [D] all the above
613. If the night patrolman does not turn up even after 15 minutes beyond the schedule arrival time, SM shall stop all the trains and issue caution order restricting the speed to []
 [A] 40 kmph [B] Spl. C.O [C] stop dead and 10kmph [D] stop dead and 15kmph
614. Maximum number of wagons containing explosives permitted by goods trains is []
 [A] Three [B] Five [C] Ten [D] any number
615. Minimum number of wagons required to be given as support wagons from B V / Passenger coach / other inflammables when explosives are carried by a train are []
 [A] three [B] five [C] ten [D] one
616. The liquids, the vapours of which have flash point below 23° C classified under Class []
 [A] 'C' [B] 'A' [C] 'B' [D] Not classified

617. Class 'A' POL product when carried, minimum number of wagons given as support wagon from electric loco and from brake van or passenger carriage are []
[A] 1 and 5 [B] 1 and 3 [C] 1 and 1 [D] 5 and 5
618. Tank wagons containing petroleum and other inflammable liquids not to be carried together With wagons containing []
[A] liquid air [B] liquid oxygen [C] both A and B [D] none of these
619. To attach a dead engine to a train, a certificate of 'fit to run' is required, which shall be issued by []
[A] Section Engineer [B] Power controller [C] Loco Inspector [D] any of the above
620. Number of dead engines is/are permitted to attach to passenger carrying train []
[A] any number each after six coaches [B] one [C] two [D] nil
621. Under any circumstances, no dead engine should be attached to any []
[A] Passenger train [B] CC rake goods [C] Rajdhani/Shatabdi [D] Mail/express
622. Officers inspection carriages are not to be permitted by []
[A] Race specials [B] Postal express trains [C] Military specials [D] All the above
623. One of the following can be attached in excess of the permitted load. []
[A] Party Coach [B] Parcel Van [C] Officer's Saloon [D] Pantry Car
624. A mail/express train shall have after loco in front and in rearmost at least one []
[A] Brake Van [B] Anti Telescopic or Steel Bodied SLR [C] Saloon [D] Dead Loco
625. No. of coaches permitted In rear of rear SLR excluding one Inspection carriage for express trains.[]
[A] Three [B] One [C] Two [D] Any No.
626. At standard – II R interlocked station the maximum speed permitted for the train over main line points is[]
[A] 140 kmph [B] 75 kmph [C] 160 kmph [D] 110 kmph
627. In case of train shunting, written instructions will be given in form No.[]
[A] T/811 [B] T/409 [C] T/806 [D] T/512
628. On Double line, to perform shunting beyond LSS, authority is[]
[A] T/806 with P.N [B] shunt signal below LSS taken 'off'
[C] LSS lever key [D] any one of the above
629. On double line, when shunting is permitted beyond LSS in SWR in rear of a travelling away train, the authority is[]
[A] T/806 without P.N [B] T.409 [C] either 'A' or 'B' [D] T/806 with P.N
630. On S/L token less sections, to perform shunting beyond LSS and up to FSS, authority is []
[A] T.806 + shunt key or P.N [B] shunt signal below LSS taken 'off'
[C] T/806 only [D] T/806 +written memo to come back

631. On double line, to perform shunting beyond Outer most facing points/BSLB, the authority is []
 [A] T/806 + P.N [B] T/806+ shunt key
 [C]T/806 only [D] T/806 +written memo to come back
632. Maximum number of persons other than the Loco Pilot/Motorman or Guard are authorized to travel in the Cab of EMU/MEMU with special permits[]
 [A] one [B] two [C]three [D] four
633. The test should be conducted before taking out MEMU/EMU on the 1st daily service run from MEMU/EMU shed, stabling siding and platform line is[]
 [A] joint brake test [B] LP&ALP check [C] LP & TXR [D] none of these
634. EMU/MEMU shall be protected as per Rule 6.03/9.10, If the detention exceeds or it is likely to exceed[]
 [A] 5 minutes [B] 10 minutes [C]15 minutes [D] none of these
635. In-charge of pilot sent to siding shall be[]
 [A] Loco pilot [B] Competent authority of siding
 [C] Guard or any person deputed by SM [D] guard only
636. Guards/Loco Pilots of all trains who are provided with VHF sets shall inform the Station Master/controller when passenger /goods trains are delayed in the block section for over.[]
 [A] 10 / 15 Min [B]5 / 15 Min [C]10 / 20 Sec [D]10 / 20 min
637. An example of consequential accident is
 [A] Signal Passing At "ON" [B] Entering Into B/S W/O ATP
 [C] Fire On Train [D] Averted Collisions
638. An example of indicative accident is
 [A] Passing Stop Signal At "ON" [B] Fire On Train [C] Collisions [D] LC Gate Accidents
639. Passing stop signal at Danger is this type of accident.
 [A] Collisions [B]Averted Accident [C] Breach Of Block Rule [D] Indicative Accident
640. In an accident if the damage to Railway property exceeds Rs 2 CRORES ,such accident shall be treated as
 [A] Serious Accident [B] Collision [C] Averted Accident [D] SPAD
641. To treat as averted collision, outside station limits, the distance between two trains shall be.
 [A] Less than 600M [B] Less than 400M [C]Less than 100M [D] Less than 180M
642. When persons are knocked down or run over and dead, no responsible person is available, body shall be[]
 [A] ignored [B] inform at next station [C] drop a memo while runs through
 [D] Handed over the dead body at nearest gate lodge or station with a memo
643. An example of breach of block rules is

- [A] Train entered into wrong line [B] train entered into B/S without a ATP
[C] Train entered into siding [D] all the above
644. Accident siren when accident takes place at out station, main line obstructed and MRT required is [
[A] Four Long [B] Three Long One Short [C] Four Long One Short [D] Three Long
645. The target time for turning out ART day and night is[]
[A] 15minutes & 20 minutes [B] 30 minutes & 45 minutes
[C] 1 hour and 1 ½ hour [D] none of these
646. The target time for turning out MRT for direct/indirect dispatch. is[]
[A] 15 minutes and 20 minutes [B] 30 minutes and 45 minutes
[C] 10 minutes and 15 minutes [D]15 minutes and 30 minutes
647. Whenever accident takes place, GLP has to prepare report in forms No.[]
[A]Acc. 1 [B]Acc. 2 [C]Acc. 3 [D] Acc. 9
648. On complete arrival of the Pilot inside the fouling mark and after verifying the LV number, the Pilot in charge intimate SM by
[A] Endorsement in Pilot movement register [B] exchange of PN
[C] Endorsement in the TSR [D] waving of hand/white light day/night
649. The Guard shall indicate the complete arrival of the train where BPAC is not provided for a stopping train when walkie talkie is working by[]
[A] waving of hand/ white light [B] writing PN in train intact register
[C] issuing a PN on walkie-talkie [D] talking on walkie talkie to SM
650. The Guard shall issue a PN to the SM at stations not provided with BPAC for a stopping train after ensuring []
[A] train comes to a stop at the station [B] train clears the block section
[C] train runs through station [D] train arrived completely and standing within fouling mark
651. Train Intact Register is in the form number []
[A] T.1420 [B] T.1410 [C] T.1510 [D] T.720
652. When walkie talkie is not working the Guard shall indicate the complete arrival for a stopping train where BPAC is not available by
[A] waving of hand/ white light [B] writing PN in train intact register
[C]Personally coming to SM office and giving PN [D] talking on CUG phone to SM
653. List of stations, number of reception lines at these stations which require exchange of Private numbers by the Guard to ensure complete arrival with provision of BPACs, shall be circulated through. []
A] Sign On register [B] additional LR trips [C] Caution Order [D] SOB.
654. As and when there is change of traction the Loco Pilot/ Guard should[]
[A] release the formation [B] conduct GLP check
[C] conduct brake continuity test [D] conduct brake continuity test / release the formation

655. The Whistle code to be given while approaching Level crossing gates is[]
 [A] Intermittent long [B] Intermittent short [C] Continuous long [D] One long one short
656. During dense fog maximum speed of a train on Automatic block system when it is showing single yellow light shall be restricted to[]
 A) 25kmph B) Restricted speed to stop at next stop signal C) 60kmph D) 30kmph
657. During dense fog maximum speed of a train on Automatic block system when signal showing two yellow lights shall be restricted to []
 A) 25kmph B) Restricted speed to stop at next stop signal C) 60kmph D) 30kmph
658. In case speedometer of loco is defective on run in the section it can be worked
 [A] with 40 kmph [B] with repair or relief engine arranged
 [C] upto shed [D] upto next crew changing point with 10% reduced speed
659. In case speedometer is defective in loco at a crew changing point it can be worked []
 [A] with 40 kmph [B] with repair or relief engine arranged
 [C] upto loco shed [D] upto next crew changing point with 10% reduced speed
660. Dummy wagons for the POL product from the Loco and BV is not required when []
 [A] Engine attached in rear [B] 8-wheeler BV is provided
 [C] 4-wheeler is attached in front and rear [D] explosive wagons are attached in rear
661. How the Guard will know about the application of brakes by the LP []
 [A] talking with LP on walkie-talkie [B] physically seeing train reduction of speed
 [C] Drop in BP pressure gauge of BV [D] Drop in FP pressure gauge of BV
662. Universal key is provided with the Guard in his personnel equipments to ensure []
 [A] Carriages are locked after passengers entrain [B] SLR is locked if not leased
 [C] SLR is locked if leased [D] luggage portion is closed and locked
663. For originating train, responsibility for closing the compartment of front/Middle SLR lies with[]
 [A] LP and ALP [B] Guard of train [C] TXR staff [D] SM of the station
664. Before leaving BV/SLR of the train the Guard shall []
 [A] lock the BV/SLR [B] apply the hand brakes of BV/SLR
 [C] endorsement is made in rough journal [D] drop in BP pressure
665. After clearance of the loop line cross-over points, when a train passes through loop lines at a station the LP and Guard shall []
 [A] look for T/P or T/G board [B] ask SM whether to proceed with normal speed
 [C] guard to inform on walkie talkie [D] exchange all right signals
666. LP and Guard notice Flat tyre on Run in Block Section should clear block section with a speed restriction of[]
 A) 15 kmph B) 30 kmph C) 50 kmph D) 75 kmph

667. The speed that a empty goods/passenger train can run after inspection of the section where flat tyre is detected upto USFD test is done is []
 A] 15 kmph B] 30 kmph C] 50 kmph D] 75 kmph
668. The speed that a loaded goods train can run after inspection of the section where flat tyre is detected upto USFD test is done is []
 A] not permitted B] 30 kmph C] 50 kmph D] 75 kmph
669. speed that a empty goods/passenger train can run after inspection of the section where flat tyre is detected after USFD test is done for the first 24 hours is []
 A] 15 kmph B] 30 kmph C] 50 kmph D] 75 kmph
670. The speed that a loaded good train can run after inspection of the section where flat tyre is detected after USFD test is done for the first 24 hours is []
 A] 15 kmph B] 30 kmph C] 50 kmph D] 75 kmph
671. To permit pilot into siding with engine pushing, the following condition(s) shall be fulfilled []
 A) Gradient not steeper than 1 in 400 enroute, B) no non-interlocked gate enroute
 C) station yard Isolated from siding line. D) all the above
672. Best method among Isolation is ---- []
 A) Buffer Stop B) Trap Point C) Sand Hump D) Scotch Block
673. Number of gauges available on Secunderabad Division are ----- []
 A) one B) two C) three D) none
674. CSR means ----- []
 A) Common standing room B) Clear Standing Room
 C) Case Steady Record D) Common Steady Room
675. The systems of working in force on SC/HYB Division is/ are []
 A) Absolute Block system B) Automatic Block system C) A & B D) none of the above.
676. The item phased out from use on IR recently and replaced by flasher hand signal lamp is- []
 A) Detonator B) H/S flag C) Fusee D) Torch
677. While receiving a train on an obstructed line on calling on signal, the train should be stopped at ----
 -- meters from the obstruction []
 A) 45 m B) 60m C) 70m D) 50m
678. The shunt signal placed in color light area is --- -- []
 A) Disc Type B) Semaphore C) Position light D) None
679. Type of Inter locking at SC station is. []
 A) Solid state Interlocking. B) RRI C) VDU D) P.I

680. The standard composition of a BOXN rake is -----[]
 A) 59+BV B) 42+BV C) 47+BV D) 56+BV
681. The standard composition of BCN rake is ----- -[]
 A) 59+BV B) 42+BV C) 47+BV D) 58+BV
682. Type of Inter locking at KCG station is. []
 A) E.I. B) RRI C) P.I D) None of these
683. ----- is the index of efficiency of passenger operations.[]
 A) Punctuality B) Speed C) C.O D) Earnings
684. ----- is the index of efficiency of goods operations.[]
 A) Punctuality B) Speed C) C.O D) Earnings
685. Quarterly safety bulletin on S.C.Rly is known as -----[]
 A) VIGIL B) Fly Leaf C) JPO D) Gazette
686. Jurisdiction of HYB Division is covering ---- number of states.[]
 A) one B) two C) three D) Four
687. For the purpose of weather warning HYB Division area falls under-----Zones. []
 A)) Four(i, ii, iii &iv) B) two (vi &vii)
 C) three(iii,vi&vii) D) Five (i, ii,iii,vi&vii)
688. LC Gates census are made once in ----- years to review the classification. []
 A) FIVE B) two C) three D) Four
689. LC Gates census are conducted for a period of ----- Days[]
 A) 1 B) 3 C) 7 D) 4
690. No. of items which constitute the brake van equipment are ----- []
 A) 5 B) 3 C) 7 D) 4
691. Maximum speed of 140 T Hydraulic Crane (BG New) is.[]
 [A] 40 KMPH B] 60 KMPH [C] 80 KMPH [D] 100KMPH
692. POH interval of passenger coaches run on Mail Exp/Passenger trains is[]
 [A] 6 months [B]12 months [C] 18 months[D] 24 months
693. Maximum speed of 140 T Hydraulic Crane (BG old) is.[]
 [A] 40 KMPH B] 60 KMPH [C] 75 KMPH [D] 100KMPH
694. Different types of maintenance of Passenger carrying trains are[]
 [A]Primary [B] Secondary [C] Terminal attention [D] all the above
695. The period of interval of IOH of passenger coaches is between[]
 [A]12 months [B] two POH [C] 24 months [D] three POH

Simple Arithmetics

1. Which of following fraction is equal to $\frac{3}{7}$ []
A) $\frac{6}{7}$ B) $\frac{3}{14}$ **C) $\frac{9}{21}$** D) $\frac{9}{14}$
2. 0.666 can be written as the following fraction []
A) $\frac{5}{7}$ B) $\frac{6}{7}$ C) $\frac{3}{5}$ **D) $\frac{2}{3}$**
3. $1.5 \times 1.5 \times 1.5 = []$
A) 33.75 **B) 3.375** C) 0.3375 D) 337.5
4. $25 + 5 \times 25 - 15 \div 3 = []$
A) 145 B) 175 C) 745 D) 485
5. $55 + 32 - 78 + 13 = []$
A) 32 **B) 22** C) 23 D) 33
6. $2 + 12(2 + 13) - 18 = []$
A) 164 B) 196 C) 195 D) 205
7. Which of the following is a prime number ? []
A) 33 B) 81 C) 93 **D) 97**
8. The smallest 3 digit prime number is: []
A) 101 B) 103 C) 109 D) 113
9. The smallest 4 digit number is []
A) 999 B) 9999 **C) 1000** D) 1001
10. The largest 3 digit number is []
A) 999 B) 100 C) 1000 D) 101
11. How many odd numbers are there between 10 to 20? []
A) 6 B) 4 **C) 5** D) 7
12. In the following numbers, which number is divisible by 4 ? []
A) 477 **B) 516** C) 625 D) 710
13. In the following numbers, which number is divisible by 5? []
A) 471 B) 516 **C) 625** D) 726
14. In the following numbers, which number is divisible by 3? []
A) 477 B) 517 C) 625 D) 710
15. In the following numbers, which number is divisible by 2? []
A) 1002 B) 2001 C) 5003 D) 719

16. In the following numbers, which number is divisible by 7? []
A) 477 B) 517 C) 625 **D) 672**
17. At what rate percent on simple interest will Rs.750 amount to Rs.900 in 5 years? []
A) 2 % **B) 4%** C) 5% D) 6%
18. 36 men can complete a piece of work in 18 days. In how many days will 27 men complete the same work? []
A) 18 **B) 24** C) 36 D) 12
19. A person purchased a cycle for Rs.1,800 and sold it to Rs.1980. What is the percentage of Profit ?
A) 12 % B)14% C) 15% **D) 10%**
20. A person purchased a scooter for Rs.20000 and sold it to Rs.21000/- What is his percentage of Profit/Loss?
A) 12 % B)14% **C) 5%** D) 10%
21. $3+33+333+3333=$ []
A) 3669 B)3999 C) 3602 **D) 3702**
22. $48/12+4 \times 25/5=$ []
A)24 B) 21 C)18 D)15
23. $261/? \times 15 + 270 = 405$ []
A)24 B) 25 **C)29** D) Non of these.
24. $47 + 345/15 \times 2 =$ []
A) 103 **B)93** C) 87 D)83
25. $3.2 \times 2.1 \times 1.6 =$ []
A)10.732 **B) 10.752** C) 10520 D) 10.270
26. $65 \times 15/? = 195$ []
A) 5 B) 15 C) 6 D) 25
27. $6389 - 1212 - 2828 = ?$ []
A)2349 B) 2493 C) 2549 D) 2394
28. $(749 - 325 - 124)/(1250 - 1100)$ []
A) 2 B) 4 C) 6 D) 8
29. $34.36 - 45.67 + 86.56 = ? + 37.96$ []
A) 36.29 B) 32.29 **C) 37.29** D) 37.49
30. 30% of 5760 is []
A) 192 B) 2420 **C) 1728** D) 1490

Official Language

1. In terms of Article ----- of The Constitution of India, Hindi language in Devanagari script shall be the official language of the Union.[]
A) 370 B) 343(2) C) 343(1) D) 342(1)
2. Article 343 (2) of the Constitution of India empowers-----to authorize use of Hindi in addition English.[]
A) International form of Indian numeral B) Roman numbers
C) capital letters D) none of these.
3. The Official Language Act was passed in .[]
A)1963 B) 1950 C)1947 D)1960
4. According to Official Language Rules, India is divided into---- regions and they are----- . [] ,
A) 3 ,A, B &C B) 2, A&B C) 3, X,Y &Z D) 2, NORTH & SOUTH
5. Which two states that come under Region A?[]
A) UP & AP B) TN& ASSAM C) MP&UP D) Kerala & Karnataka
6. What are the States that come under Region B?[]
A) UP & AP B) Gujarat& Punjab C) MP&UP D) Kerala & Karnataka
7. Which two states s that come under Region C?[]
A) UP & AP B) TN& GUJARAT C) MP&UP D) Kerala & Karnataka
8. Communications from Central Government Offices to the States, Offices and persons in Region shall be in Hindi, and if it is in English, a Hindi translation shall accompany.[]
A) A B) B C) C D) none of these
9. Communications from Central Govt. Offices to States or Offices in region shall be in Hindi, and if it is in English, Hindi translation shall accompany[]
A) A B) B C)C D) none of these
10. Communications from Central Govt. Offices to persons in Region B shall be in .[]
A) Hindi B) English C) Hindi & English D) English/Hindi
11. Communications from Central Government Offices to States or Persons in Region C shall be in []
A) Hindi B) English C) Hindi &English D) English or Hindi
12. Communications between Central Government Offices between one Ministry or Department and another may be in [] .
A) Hindi B) English C) Hindi &English D) English/Hindi
13. Communications between Central Government Offices between one Ministry or Department and attached/subordinate offices in Region A may be in depending on number of persons having another may be in []

- A) Hindi B)English C) Hindi &English D) English/Hindi
14. Communications between Central Govt. Offices in Region A shall be in .[]
A) Hindi B) English C) Hindi &English D) English/Hindi
15. Communications between Central Govt Offices in Region B or C may be in .
A) Hindi B) English C) Hindi &English D) English/Hindi
16. Translations of such communication shall be provided along with the communication where it is addressed to Offices in .[]
A) A region B) B region C)A&B regions D) C region
17. Representations, when made/signed in Hindi shall be replied to in .[]
A) Hindi B) English C) Hindi &English D) none of these
18. Noting in Central Government Offices may be made by an employee in -----(Hindi)for which translationwill not be askedby the officer unless it is legal/technical in nature.[]
A) Hindi B) English C) Hindi &English D) none of these
19. If an employee has working knowledge of Hindi, he will not ask for English translation of a Hindi Document, unless it is of nature.[]
A) Non -technical B) technical C) Clumsy D)none of these
20. Manuals, Codes, Forms, Notices etc., shall be printed or cyclostyled in form.[]
A) Hindi B)English C) Hindi &English D) none of these
21. The forms and heading on registers shall be in .[]
A) Hindi B)English C) Bilingual D) English/Hindi
22. All name plates, sign boards, letter heads, inscriptions on envelopes & other stationery etc. shall be in [] .
A) Hindi B) English C) Bilingual D) English/Hindi
23. Responsibility for compliance of the Official Language Rules shall be that of .[]
A) Administrative head/Head of the office.. B) Head of the office
C) Administrative head D) None of these
24. Chairman of the Kendriya Hindi Samithi(KHS)-----[]
A) President B) Prime Minister C)Vice -President D) Home Minister
25. Chairman for committee of Parliament on official language.-----[]
A) President B) Prime Minister C)Vice -President D) Minister of Home affairs
26. Number of committee members for committee of Parliament on official language []
A) 15 B) 20 C)30 D) 40
27. Hindi Divas celebrated on -----[]
A) 15th August B) 26th Jan C)14th Sep D)Oct'20TH
28. Chairman of Railway Hindi Advisory committee
A) Minister for Railways B) Prime Minister C)President D) Vice -President

29. Chairman of Zonal official language implementation committee[]
 A) Minister for Railways B) GM C) SDGM D)PCOM
30. Chairman of Divisional official language implementation committee[]
 A) GM B) DRM C) Sr.DOM D)RBA

Establishment

1. As per VIIth Pay Dress allowance for PM []
 (A) Rs 6000 p.a (B) Rs 10000 p.m (C) Rs 5000 p.a (D) Rs 10000 p.a.
2. The Minimum pension as per VIIth Pay commission[]
 (A) Rs 3500 (B) Rs 8500 (C) Rs 9000 (D) Rs 1050
3. Composite transfer grant as per VII PC is equivalent to[]
 (A) 80% pay (B) 70% pay (C) 65% pay (D) 35% pay
4. Suspension is -----[]
 A) Minor Penalty B) not a Penalty C) Major Penalty D) Non of the above
5. Censure is a -----
 A) Minor Penalty B) not a Penalty C) Major Penalty D) Non of the above
6. Dismissal is a ----- Penalty.[]
 A) Minor Penalty B) not a Penalty C) Major Penalty D) Non of the above
7. Maternity leave permissible for a period of []
 [A]90 days [B]120 days [C] 135 days [D] 180 days
8. From the date of confinement Paternity leaves to be availed within. []
 [A] 12 months [B] 24 months [C] 6 months [D]48 months
9. Which form is used for imposition of minor penalty.[]
 A) SF-5 B) SF-7 C) SF-11 D) SF-1
10. Which form is used for imposition of major penalty.[]
 A) SF-5 B) SF-7 C) SF-11 D) SF-1
11. Paternity leave permissible for a period of []
 [A]20 days [B]12 days [C] 15 days [D] 30 days
12. Child Care leave permissible for a period of []
 [A]90 days [B]720 days [C] 735 days [D] 730 days
13. How many days of LAP in a calendar year, a permanent/ Temporary Railway servant shall

- be entitled to get? []
 A) 30 days B) 15 days C) 20 days D) 45 days
14. How many days of LHAP can be accumulated to an employee in his total service[]
 A) 300 days B) 450 days C) 600 days D) unlimited
15. Maximum encashment of leave on average pay is []
 A) 20 days B) 30 days C) 60 days D) 180 days
16. Maximum no of persons allowed on a Privilege pass when dependents are included is[]
 [A]3 [B] 5 [C] 7 [D] no limit
17. Maximum amount of Retirement Gratuity payable []
 [A] Rs20 Lakhs [B] Rs10 Lakhs [C] Rs25lakhs [D] Rs15lakhs
18. Maximum no of dependents allowed on a Privilege pass is []
 [A] 1 [B] 2 [C] 3 [D] 4
19. Children's Education allowance is permissible for how many no of surviving children[]
 [A] 3 [B] 4 [C] 2 [D] 1
20. Of late validity for a Privilege Pass/PTO is ?[]
 (A) 3 months (B) 4 months (C) 2 months (D) 5 months
21. The colour of the First Class A Pass is _____ []
 [A] White [B] Pink [C] Green [D] Yellow
22. The colour of the First Class Pass is _____ []
 [A] White [B] Pink [C] Green [D] Yellow
23. The colour of the Second Class Pass is _____ []
 [A] White [B] Pink [C] Green [D] Yellow
24. How many days of CL's in a calendar year, a permanent/ Temporary Railway servant(Open line) shall be entitled to get? []
 A) 30 days B) 10 days C) 20 days D) 15 days
25. Post Retirement Complimentary Pass are admissible to Railway Servant retired after putting ____ years of service []
 [A] 20 [B] 12 [C] 15 [D] 16
26. When dependents are included in a Pass/PTO, number persons entitled to be include in Pass/ PTO Shall be []
 [A] All Family members + 2 dependents [B] 5 member's only
 [C] 6 members only [D] Any number of Family members + 3dependents
27. In case of loss of IInd class Privilege Pass ----- amount has to be levied as fine []
 [A]Rs. 5 [B]Rs.10 [C]Rs. 15 [D] Rs. 25
28. Attendants of Pass Holder is []
 (A)Part time servant (B)Servant (C)Full time paid servant (D)Any person
29. Maximum days of leave on average pay that can be accumulated is []

A) 120 days B) 180 days C) 190 days D) 300 days

30. Appeal shall be entertained unless preferred within _____ days []
[A] 100 [B] 10 [C] 30 [D] 45

General English & General Knowledge

1. Kamala's fountain pen is ----- shyma's []
A) as expensive B) expensive than C) expensive D) to expensive than
2. The number of school dropouts ----- quite disturbing []
A) a B) are C) was D) were
3. She has never ----- with his working as a clerk
A) satisfy B) satisfied C) to satisfy D) been approve
4. At ----- station, I will hire a coolie to carry my baggage
A) a B) the C) an D) none of the above
5. The number of marks carried by each question ----- indicated at the end of the question. []
A) is B) are C) were D) not required
6. It is necessary that everybody ----- have a house. []
A) must B) should C) could D) would
7. I ----- tennis every day.
A) play B) playing C) am playing D) am play
8. How many students in your class have ----- from village?
A) came B) coming C) come D) are coming
9. I think I ----- a new calculator for tomorrow's maths class.
A) needs B) need C) am needing D) needed
10. The phone ----- can you please answer it?
A) ring B) have ring C) is ringing D) rang
11. She is married ----- an engineer.
A) to B) with C) for D) not required.
12. That job is perfect ----- him.
A) for B) to C) with D) not required

13. She is beautiful -----her.
A) to B) then C) than D) with
14. I did not -----him yesterday.
A) see B) saw C) seen D) have seen
15. Competency certificate for persons authorized ----- drive tamping machine is essential.
A) for B) from C) to D) with
16. The official-----charge shall bring the machine to a stop outside the advanced starter. []
A) in B) of C) by D) with
17. There was -----rainfall last year.
A) few B) less C) fewer D) lesser
18. There are -----students in the class.
A) few B) for C) an D) from
19. It is ----- old television set.
A) a B) the C) an D) none of the above
20. I ----- drive because I passed the driving test.
A) may B) shall C) can D) will
21. I've been in America -----3 months.
A) since B) from C) for D) by
22. At the party, I didn't meet -----.
A) Everyone B) anybody C) nobody D) each one
23. They organized the party for -----
A) themselves B) them self C) their self D) their selves
24. She is----- than Sita.
A) tall B) taller C) very tall D) tallest
25. The sun rises in ----- east.
A) at B) from C) the D) with
26. They do ----- lot of shopping.
A) an B) the C) a D) not required
27. I do not want to ----- the game.
A) lost B) lose C) loss D) losing
28. You are ----- to complete the assignments.
A) Suppose B) supposed C) supposing D) to suppose

29. Let ----- go.
A) his B) he C) him D) himself
30. The two brothers love -----other.
A) each B) one C) every D) between
31. I -----waiting for you in the office for the last two hours.
A) was B) have C) have been D) has been
32. I -----my project yesterday.
A) complete B) completed C) completing D) am completing
33. Ram is blind-----one eye.
A) with B) in C) for D) to
34. One should realize -----responsibilities.
A) his B) their C) one's D) one
35. She is ----- to music.
A) listen B) listened C) listening D) for listen
36. The ticket grants admission ----- the show.
A) to B) by C) with D) from
37. Ram has been playing cricket ----- morning.
A) from B) for C) since D) early
38. If I -----a bird, I would fly.
A) has B) were C) are D) have
39. If I ----- to Delhi, I will meet her.
A) will go B) go C) goes D) am going
40. They -----for shopping last weekend.
A) gone B) went C) going D) go
41. I was ----- many movies back to back during vacation.
A) looking B) seeing C) watching D) gazing
42. She ----- her essay last Friday.
A) Submitted B) will submit C) is submitting D) submit
43. They ----- for yoga every day.
A) go B) will go C) shall go D) goes
44. Scientists -----conducting studies on individual genes for years.
A) have B) have been C) has D) has been

45. Unless you -----hard, you will not pass.
A) work B) working C) worked D) works
46. This news was ----- from all India radio yesterday.
A) have broadcasted B) broadcasting C) broadcasted D) been broadcast
47. Hard work and honesty ----- needed for success in life.
A) are B) were C) is D) was
48. I have learnt this lesson word -----word.
A) for B) from C) by D) with
49. The snake ----- we saw in the forest was a Cobra.
A) which B) who C) whom D) none of these.
50. She's the girl ----- we saw in the Railway station.
A) who B) whom C) when D) where
51. Everyone on the project have to down load the plan ----- play store.
A) from B) had C) have D) is
52. Neither he nor his bodyguards ----- there.
A) are B) from C) were D) at
53. After he had finished his performance he ----- to home.
A) go B) gone C) by D) went
54. Guard of the train shall ensure----- departure of train that the BV Equipment is correctly available.
A) before B) from C) on D) after
55. They asked me ----- my job.
A) for B) from C) by D) about
56. She was late for duty and -----punished for that.
A) for B) was C) by D) from
57. You-----get all the information if you read this book carefully.
A) won't B) from C) can D) to
58. He ----- been working in a bank for past 5 years.
A) has B) was C) from D) have
59. Each of the boys ----- paid the tuition fee.
A) for B) from C) has D) to

60. Had I known it earlier I ----- contacted you.
A) would have B) will C) from D) have
61. The person ----- was recommended for this position did not fulfill prescribed norms. []
A) where B) who C) whom D) can
62. Why ----- professor Gagan spend so many hours in the laboratory?
A) can B) from C) this D) does
63. The population of Mumbai is higher -----that of Delhi.
A) than B) on C) by D)of
64. As I had arrived the station, the train---- the platform.
A) leave B) live C) left D) none of these
65. One ----- my favourite actors is acting in this play.
A) is B) have C) by D) of
66. If there is no train ----- you will go there?
A) for B) from C) how D) why
67. He ----- in such a hurry that he didn't wait for me.
A) is B) are C) go D) was
68. The maximum speed permissible ----- 1 in 8 ½ turn outs with curved switches of 52/60 KG Rails on PSC sleepers should be 15 KMPH.
A) over B) on C) at D) where
69. They ----- been very close friends till they quarrelled.
A) would B) from C) have D)were
70. You ----- remind me to post the letter.
A) were B) have C) will D) must
71. I shall certainly write you----- I reach Bangalore.
A) when B) where C) after D)before
72. On the ring road we witnessed the collision----- truck and auto
A) at B) between C) by D)with
73. Mr. Patel has not been ----- office for the last one month.
A) for B) at C) by D) attending
74. Azaruddin is ----- of the finest batsmen that India have ever produced.
A) for B) great C) one D) big

75. The thief broke ----- house at the dread of night.
A) go B) went C) the D) into
76. May I know ----- you want to see please?
A) who B) whom C) where D) why
77. He said that he ----- mind if I refused his offer.
A) who B) can C) would D) will
78. Though child marriage ----- banned, the custom still prevailed among some groups. []
A) has been B) will C) why D) can
79. Fate smiles those who untiringly grapple with stark realities of life.
A) On B) are C) were D) can
80. I saw a of cows in the field.
A) heap B) crowd C) herd D) cub
81. Success in this examination depends hard work alone.
A) with B) from C) by D) On
82. Railway servant who is ----- to attend the duty by reason of sickness, shall produce a sick certificate from a competent medical authority without delay.
A) at B) from C) unable D) available
83. Any Railway servant, shall not smoke when dealing ----- public or on the platform.
A) for B) from C) by D) with
84. Whenever any amendment is issued to rule book acknowledgement of all staff working at that station ----- be obtained.
A) is B) shall C) can D) are
85. The help of C&W staff should be ----- when air pressure trouble occurs within the station limits.
A) care B) while C) taken D) given
86. Guard of the train shall travel ----- the engine, when train is to run without Brake van. []
A) at B) from C) by D) in
87. The vehicle or load or train shall be ----- the fouling mark.
A) out side B) from C) within D) at
88. The train be chained and padlocked using ----- two chains one at either end. []
A) with B) at least C) by D) below
89. At least four wooden wedges or iron skids be used, two each ----- the outermost pair of wheels at either end. []
A) for B) below C) by D) at

90. Hand brakes of at least six wagons from----- end must be fully tightened.[]
A) for B) from C) by D) either
91. In case coaching vehicles are stabled Guards hand brakes in SLR----- be applied.[]
A) must B) may C) by D) can
92. The points must be set clamped and padlocked----- the blocked line and towards dead end or trap point.[]
A) for B) with C) against D) by
93. ----- vehicles are uncoupled the hand brakes should be applied.[]
A) before B) from C) by D)to
94. Before uncoupling wooden wedges or iron skids should be used to prevent vehicles----- rolling down.[]
A) for B) front C) by D) from
95. As far as possible vehicle or load or train should be stabled on a line which is isolated----- other running lines.[]
A) for B) from C) by D) at
96. The speed of trains----- Non Interlocked facing points shall not exceed 15 KMPH. []
A) Over B) from C) by D) at
97. The train may run over Interlocked facing points at such speeds as may be permitted----- the standard of Interlocking. []
A) for B) from C) by D) on
98. The speed over the turn outs having 1 in 8 ½ straight switch ----- be restricted 10KMPH for passenger carrying trains and 15 KMPH for Goods trains.[]
A) to B) from C) should D) with
99. The last vehicle of train shall be indicated ----- placing a tail board/tail lamp. []
A) for B) from C) by D) with
100. The dead locomotive shall be attached ----- to train engine only.
A) for B) next C) by D)with
101. Sick coaches should be properly locked and windows secured so as to ----- entry of any passengers into these coaches.
A) for B) from C) by D) Prevent
102. Stop hand signal is indicated at day time by showing red flag or by raising both arms with hands -- ---- the head.
A) above B) from C) by D)with

103. Stop hand signal is indicated at night time by showing red light or by violently waving white light horizontally----- the body.
A) by B) from C) across D)with
104. ----- foggy weather the speed shall not exceed 60 KMPH in absolute block system.
A) the B) during C) by D)with
105. When an assisting engine is attached in rear of last vehicle of a train, the tail board shall be fixed--
----- the assisting engine.
A) on B) in C) by D) behind
106. A Light engine ----- in a block section shall have marker lights on during day or night. []
A) Moving B) from C) by D) with
107. In case of obstruction on track guard must ----- a red flashing hand signal lamp at night or a red flag during day.
A) Show B) has C) Seen D) with
108. If the chain has been pulled, the guard shall----- the occupants of coach and tries to find out name and address of person who used it.
A) for B) Show C) be D) Question
109. The guard shall ----- the fact regarding ACP in the CTR and shall send a special report to the DRM. []
A) record B) from C) be D)with
110. Running of trains without Brake-van is strictly----- during total failure of communication. []
A) for B) from C) prohibited D)with
111. The number of persons permitted to travel in Brake-van of Goods train in addition to guard should not ----- five.
A) less than B) from C) exceed D)with
112. In case of express trains a maximum of two coaches may be attached in ----- of the rear SLR.[]
A) for B) rear C) by D)with
113. In case of Goods trains a maximum of two bogies or their equivalents may be ----- in rear of the rear Brake-van.
A) Below B) low C) by D) attached
114. All the ----- in connection with working of trains must be reported in combined train report (CTR) []
A) Information B) from C) irregularities D)with
115. The guard of train must, at the -----of each trip make over his CTR to the SM for submission to DRM.
A) Start B) end C) middle D) none of the above

116. The Vehicle Guidance (VG) must be carefully and legibly prepared in -----at the starting station. []
A) ink B) Platform C) book D) Train
117. The loco pilot of a train shall not pass an outer, a home or a routing signal that refers to him, when it ----- 'on' or defective.
A) for B) from C) is D)with
118. Normal authority to ----- on single line token section is token.
A) proceed B) from C) be D)was
119. Authority for the material train after----- of work coming back to the same station is T/462. []
A) for B) completion C) station D)with
120. To send a relief engine or Train ----- occupied block section is T/A 602.
A) for B) from C) by D) into

General Knowledge

1. The First Train in India started between stations
[A] Bhorbunder and Thane [B] Varanasi and Delhi
[C]New Delhi and Chandigarh [D] none of the above
2. The First Train in India started on
[A] 16.04.1863 [B] 16.04.1853 [C]16.04.1873 [D] none of the above
3. The Indian Railway Minister
[A]Mr.Piyush Goyal [B] Mr.Sadananda Goud [C] Ms.MamataBenerji
[D] Mr.Lalu Prasad Yadav
4. Ministers of state for Railways
[A] Mr.Piyush Goyal [B] Mr.SureshAngadi [C] Ms.MamataBenerji
[D] Mr.Lalu Prasad Yadav
5. The President of India is
[A] Mr.Piyush Goyal [B] Mr.Narerndra Modi [C] Mr.Ramanath Kovind
[D] Mr.Lalu Prasad Yadav
6. The Prime minister of India is
[A] Mr.Piyush Goyal [B] Mr.Rahul Gandhi [C] Mr.Ramanath Kovind
[D] Mr.Narerndra Modi

7 .The Vice President of India

- [A] Mr.M. Venkaya Naidu [B] Mr.Rahul Gandhi [C] Mr.Ramanath Kovind [D] Mr.Narendra Modi

8. The Chief Justice of India

- [A]Mr.AravindBobde [B] Mr.Subhashan Reddy [C] Mr.Eashweraiah [D] Mr.sadanandam

9. The Chief Election Commissioner of India

- [A] Mr.RajanGogai [B] Mr.Subhashan Reddy [C] Mr.Sushil Arora [D] Mr.Sadanandam

10. Chief Minister of Andhra Pradesh

- [A] Mr.ChandraBabu Naidu [B] Mr.Y.S.Jagan Mohana Reddy [C] Mr.Pawan Kalyan [D]Mr.Raghu Veera Reddy

11. The Governor of Andhra Pradesh

- [A] Mr.BiswabhusanHaricandan [B] Mr.KonijetuRosaiah [C] Mr.Vidyasagar [D] Mr.kiranBedi Reddy

12. The Chairman Railway board

- [A] Mr.RajanGogai [B] Mr.AshwnaLohani [C] Mr.Vinod Kumar Yadav [D] Mr.Sadanandam

13. The Member Traffic

- [A] Mr.P.S. Mishra [B] Mr.AshwnaLohani [C] Mr.V.K. Yadav [D] Mr.GhanShyam Singh

14. The Railway board Head quarters

- [A] Navi Mumbai [B] Luknow [C] Kolkota [D] New Delhi

15. The GM of SC Railway

- [A] Mr.GajananMallya [B] Mr.AshwnaLohani [C] Mr.Vinod Kumar Yadav [D] Mr.GhanShyam Sing

16. The PCOM of SC Railway

- [A] Mr.GajananMallya [B] Mr.K.Shiva Prasad [C] Mr.V.KYadav [D] Mr.G .S. Singh

17. CFTM of SC Railway

[A] Mr.GajananMallya [B] Mr.N.Madhusudhan Rao [C] Mr.B.Nagya

[D] Mrs.K.Padmaja

18. CPTM of SC Railway

[A] Mr.Dhananjayulu [B] Mr.N.Madhusudhan Rao [C] Mr.B.Nagaya

[D] Mrs.K.Padmaja

19. CTPM of SC Railway

[A] Mr.A.S.Rao [B] Mr.B.Nagaya [C]] Mr.N.Madhusudhan Rao

[D] Mrs.K.Padmaja

20. CTM(G) & PP of SC Railway

[A] Mr.Dhananjayulu [B] Mr.A.J.Rathod [C] Mrs.K.Padmaja [D] Mr.B.Nagya

21. PCCM of SC Railway

[A] Mr.Dhananjayulu [B] Mr.A.J.Rathod [C] Mr.G.John Prasad [D] Mr.M.G.Shekaram

22. The PCPO of SC Railway

[A] Mr.Dhananjayulu[B] Mr.Rajeev Kishore [C] Mr.K.Shiva Prasad

[D] Mr.M.G.Shekaram

23. CCRS Head quarters

[A] Navi Mumbai [B] Luknow [C] Kolkota [D] New Delhi

24. RDSO Head quarters

[A] Navi Mumbai [B] New Delhi [C] Kolkota [D] Luknow

25. The Father of Nation

[A] Mr.Mohan Das Karamchand Gandhi [B] Mr.Rahul Gandhi

[C] Mr. Mr.Rajeev Gandhi [D] Mr.Jawahr Lal Nehru

26. The Iron man of India

[A] Mr.Mohan Das Karamchand Gandhi [B] Mr.SardarVallabha Bai Patel

[C] Mr. Mr.Rajeev Gandhi [D] Mr.Jawahr Lal Nehru

27. The Nightingale of India

[A] Mrs.Sarojini Naidu [B] Mrs.MamataBenerji [C] Mrs.Indira Gandhi

[D] Mrs.Sonia Gandhi

28. TheNational bird of India

[A] Pea Cock [B] Pigeon [C] Parrot [D] Sparrow

29. The National animal of India

- [A] Lion [B] Elephant [C] Tiger [D] Giraffe
30. The National flower of India
- [A] Lily [B] Rose [C] Lotus [D] Mogra
31. The Capital of India
- [A] Navi Mumbai [B] Luknow [C] Kolkota [D] New Delhi
32. Capital of Andhra Pradesh
- [A] Chennai [B] Rajamandry [C] Tirupati [D] Amaraavathi
33. The National game of India
- [A] Hockey [B] Cricket [C] Val bal [D] New Delhi
34. National Anthem of India.
- [A] Jana ganamana [B] Vandemaatharam [C] National pledge [D] None of the above
35. National song of India
- [A] National pledge [B] Vandemaatharam [C] Jana gana mana
- [D] None of the above
36. National flag of India was designed by
- [A] Mr.PingaliVenkayya [B] Mr.Lala Lajpat Rai
- [C] Mr.Sardar Vallabh Bai Patel [D] Mr.VinobhaBave
37. Number of states in India.
- [A] 29 [B] 28 [C] 30 [D] 7
38. Number of union territories in India.
- [A] 7 [B] 29 [C] 30 [D] 8
39. National Holidays of India
- [A] 3 [B] 5 [C] 7 [D] 8
40. Grand old man of India
- [A] Mr.PingaliVenkayya [B] Mr.Lala Lajpat Rai
- [C] Mr.Sardar Vallabh Bai Patel [D] Mr.Dada Bai Noaroji
41. Who wrote Gitanjali
- [A] Mr.Rabindra Nath Tagore [B] Mr.Lala Lajpat Rai
- [C] Mr.Sardar Vallabh Bai Patel [D] Mr.Bankim Chandra Chatterji
42. Chandigarh is the capital of
- [A] Punjab and Haryana [B] Punjab and New Delhi [C] Jammu and Kashmir

[D] None of the above.

43. CRS of SC Railway

[A] Mr.D.K.Singh [B] Mr.Ram Kripal [C] Mr.Deva Sing [D] Mr.Shekavath

44. Red-Fort is located at

[A] Chennai [B] New Delhi [C] Luknow [D] Mumbai

45. Pink city of India is

[A] Jaipur [B] New Delhi [C] Luknow [D] Mumbai

46. Garden City of India

[A] Jaipur [B] Bagalore [C] Luknow [D] Mumbai

47. Integral Coach Factory is located at

[A] Perambur [B] Bagalore [C] Luknow [D] Mumbai

48. Triveni Sangam is located at

[A] Perambur [B] Prayag Raj [C] Luknow [D] Mumbai

49. Chitaranjan loco motive works is located in

[A] Perumbur [B] Kanpoor [C] Chittaranjan [D] Varanasi

50. Rail Spring karkhana is located at

[A] Perumbur [B] Sithouli [C] Chittaranjan [D] Varanasi

51. DRM of HYB Division

[A] Mrs.Auna Singh [B] Mr.Arun Kumar jain

[C] Mrs.Vandana Singhal [D] Mr.N.S.R.prasad

52. ADRM/O/HYB Division

[A] Mrs.Auna Singh [B] Mr.HemsinghBanoth

[C] Mrs.Vandana Singhal [D] Mr.N.S.R.prasad

53. Sr. DOM of HYB Division

[A] Mrs.AnithaBaarik [B] Mr.S.V.Sai Prasad

[C] Mr.B.Venkanna [D] Mr.G.Sudhakar

54. Sr. DSO of HYB Division

[A] Mr.P.V.N.Ravi Kumar [B] Mr.S.V.Sai Prasad

[C] Mr.P. Raj Kumar [D] Mr.G.Sudhakar

55. Sr. DPO of HYB Division

[A] Mr.P.Raj Kumar [B] Mr.Sriramulu.

[C] M.G.Sudhakar [D] Mr.P.V.N.RaviKumar

56. Sr. DCM of HYB Division

[A] Mr.P. Raj Kumar [B] Mr.B.Venkanna [C] Mr.P.SaiKumar.

[D] Mr.P.V.N.Ravi Kumar

57. DOM(G) of HYB Division

[A] Dr.P.Satheesh [B] Mr.B.Venkanna [C] Mr.P. Raj Kumar [D] Mr.P.V.N.Ravi Kumar

58. Basar Station is located on the banks of _____ River.

[A] Krishna [B] Ganga [C] Godhavari [D] Kaveri

59 Kurnool Station is located on the banks of _____ River.

[A] Krishna [B] Tungabadra [C] Godavari [D] Kaveri

60. _____ temple is located near Basar Station.

[A] Sri Laxmi devi [B] SriShiva [C] Sri Vishnu [D]Sri Saraswathi

Commercial

1. PGRM stands for _____
[A] Poor Grievances Redressal Machinery
[B] Political Grievances Redressal Machinery
[C] Public Grievances Redressal Machinery [D] None
2. The Head of the Public Grievances Organization at Divisional level is
[A] Sr.DCM [B] DRM **[C] ADRM** [D] ACM
3. The Head of the Public Grievances Organization at Zonal Level is _____
[A] PCCM **[B] AGM** [C] GM [D] CPRO
4. The Head of the Commercial Department at Zonal Level is _____
[A] PCOM [B] AGM **[C] PCCM** [D] CPRO
5. The Commercial Department is responsible for _____
[A] Sale of transport [B] Creating and developing traffic
[B] Fixing of fares & freight **[D] All these**
6. The Commercial Department deals with _____ traffic
[A] Goods [B] Passenger [C] Luggage **[D] All these**
7. Platform ticket is valid for _____ Hours.
[A] 3 [B] 4 **[C] 2** [D] 1
8. Cost of platform ticket is Rs _____
[A] 3 [B] 2 [C] 5 **[D] 10**
9. Children below _____ years of age are allowed to travel free.
[A] 4 [B] 6 **[C] 5** [D] 2

10. Children of 5 years and above and below 12 years of age will be charged _____ of adult fare.
[A] Same [B] **Half** [C] 1/3 [D] 1/4
11. Boys under _____ years of age are permitted to travel in ladies compartment along with relatives/parents.
[A] 5 [B] 10 [C] 13 [D] **12**
12. Staff working on trains can keep private cash upto Rs._____
[A] 500/- [B] 1500/- [C] **2000/-** [D] 750/-
13. Stationary staff is permitted to have a private cash upto Rs._____
[A] Rs.500/- [B] Rs.750/- [C] Rs.1000/- [D] Rs.1500/-
14. No. of languages mandatory on Lower class tickets are _____
[A] One [B] Two [C] **Three** [D] Four
15. Super fast supplementary charges for II class is._____
[A] Rs.10/- [B] **Rs. 15/-** [C] Rs. 20/- [D] Rs.30/-
16. Season Tickets for general public can be given up to a distance of _____ kms.
[A] 100 [B] **150** [C] 200 [D] 250
17. Normal Season Tickets are issued for _____ periods
[A] Monthly [B] Quaterly [C] Yearly [D] **All of these**
18. Reservation on Season tickets is _____
[A] Permitted [B] **Not Permitted**
[C] Permitted Once, Monthly [D] Permitted once Quaterly
19. Season tickets can be renewed _____ days in advance of the date of expiry.
[A] One day [B] 2 days [C] 5 days [D] **10 days**
20. Season tickets are issued for travel in _____ and _____ classes only.
[A] ACCC, FC [B] **FC, II** [C] IAC, FC [D] SL, ORDINARY
21. Quarterly season ticket fare is _____ times of monthly season ticket fare
[A] **2.7** [B] 2.5 [C] 2 [D] 1.5
22. Season tickets on concession issued to general students up to maximum of _____ age.
[A] **25** [B] 27 [C] 30 [D] 35
23. M.V.S.T. is issued for _____ class only.
[A] First [B] **Second** [C] ACCC [D] FC and II
24. IZZAT season tickets are issued on collection of fare of _____
[A] Rs. 10/- [B] Rs. 15/- [C] Rs. 20/- [D] **Rs.25/-**
25. IZZAT season tickets are issued to unorganized labourers whose income is up to Rs.____month.
[A] 1400 [B] **1500** [C] 2500 [D] 2000
26. Free second class monthly season tickets are issued to **male** students studying up to _____ Standard.
[A] 11th [B] 10th [C] Degree [D] **12th**

27. Free second class monthly season tickets are issued to **female** students studying upto _____ Standard
 [A] 11th [B] 10th [C] **Degree** [D] 12th
28. MPs are issued with _____
 [A] Tourist coupon ticket [B] **ICCRP**
 [C] Rail Travel Coupon [D] HOR
29. The highest class in which MPs are allowed to travel on ICCRP _____
 [A] I AC [B] II AC [C] Executive Class [D] **Both (A) & (C)**
30. Sleeping accommodation is provided between _____ & _____ hrs
 [A] 20 & 8 hours [B] 22 & 6 hour [C] **21 & 9 hours** [D] 20 & 6 hours
31. Holders of single journey tickets for a distance of more than _____ kms are allowed to break journey enroute
 [A] 200 [B] 400 [C] 300 [D] **500**
32. Number of Break journey is permitted on tickets upto 1000 KMs distance
 [A] Two [B] three [C] **one** [D] four
33. Two break journeys are permitted on journey tickets above _____ kms.
 [A] 500 [B] 800 [C] 900 [D] 1000
34. Break journey is not permitted by
 [A] Rajdhani [B] Shatabdi [C] **Both (a) & (b)** [D] None of these
35. Number of break journeys permitted on single journey tickets above 1000 KMs.
 [A] **2** [B] 4 [C] 3 [D] 1
36. The break journey period is _____ days excluding the day of arrival and day of departure
 [A] 4 [B] 3 [C] **2** [D] 5
37. First break journey is permitted after travelling _____ KMs
 [A] 200 [B] 300 [C] **500** [D] 100
38. Maximum number of break journeys allowed on a single journey ticket is _____
 [A] 3 [B] **2** [C] 1 [D] 4
39. Halt at an intermediate station for less than _____ hours for onward connecting train is NOT treated as break journey
 [A] 10 [B] 6 [C] 12 [D] **24**
40. To avail break journey, tickets must be presented for endorsement to
 [A] S.M. [B] Booking Clerk [C] T.C. [D] **Either (A) or (C)**
41. Maximum number of break journeys permitted on a circular journey ticket is
 [A] 2 [B] 3 [C] 4 [D] **8**
42. H O R stands for _____
 [A] High official of railway [B] **High official requisition**
 [C] Higher officer in railway [D] None
43. Dropping cash bag in the safe is witnessed by _____ of the train.
 [A] Driver [B] Conductor [C] **Guard** [D] RPF

44. S.M. must deposit cash bag in the presence of _____
 [A] RPF [B] Station master [C] Goods clerk **[D] Guard**
45. Whenever cash bag is deposited in the cash safe, the signature of _____ is to be obtained by Guard in cash summary.
 [A] Guard **[B] Station master** [C] Goods clerk [D] RPF
46. Identity card issued by Railways along with season ticket is valid for _____
 [A] One year [B] Two years **[C] Five years** [D] Four years
47. After collection of cash bags in the section, the cash safe is sealed at _____
 [A] Forwarding station [B] En-route station
[C] Last cash dropping station [D] Destination
48. At the last cash depositing station, cash safe should be sealed by _____
 [A] Guard **[B] Station master** [C] TIA [D] Commercial Inspector
49. PRS stands for _____
 [A] Passenger rail services [B] Passenger rail system
[C] Passenger reservation system [D] Permanent reservation system
50. RAC means _____
[A] Reservation against cancellation [B] Reservation and cancellation
 [C] Reservation and concession [D] None
51. A.C.P. stands for _____
 [A] Automatic chain panel **[B] Alarm Chain Pulling**
 [C] Additional chain pulling [D] None
52. The following are exempted from weighment when carried as luggage
 [A] Umbrella [B] Walking stick [C] Hand bag **[D] All these**
53. Free allowance of AC FC is _____ KGs.
 [A] 60 [B] 40 [C] 50 **[D] 70**
54. Free allowance of AC 2 tier is _____ KGs.
[A] 50 [B] 40 [C] 70 [D] 35
55. Free allowance of AC 3 tier is _____ KGs.
 [A] 60 **[B] 40** [C] 50 [D] 70
56. Free allowance of FC is _____ KGs.
[A] 50 [B] 40 [C] 70 [D] 60
57. Free allowance of AC CC is _____ KGs.
 [A] 50 [B] 70 **[C] 40** [D] 35
58. Free allowance of SL is _____ KGs.
 [A] 60 **[B] 40** [C] 50 [D] 70
59. The free allowance on II Class Pass is _____ KGs.
 [A] 40 **[B] 50** [C] 60 [D] 70
60. The free allowance on I Class pass is _____ KGs.

[A] 60 [B] 50 **[C] 70** [D] 35

61. Free allowance on child ticket is _____ of free allowance of the adult ticket.
[A] Full **[B] Half** [C] Same [D] None
62. Luggage should be presented for booking at least _____ before scheduled departure of the train.
[A] 60 minutes **[B] 30 minutes** [C] 10 minutes [D] No time limit
63. Luggage can be booked _____ hours in advance excluding the day of scheduled departure of the train on reserved tickets.
[A] 12 hrs **[B] 24 hrs** [C] 48 hrs [D] 72 hrs
64. Minimum distance for charging luggage is
[A] 10 km **[B] 50 km** [C] 100 km [D] 25 km
65. Minimum weight for charge of luggage _____ Kgs.
[A] 30 **[B] 10** [C] 40 [D] 5
66. Minimum fare for charging luggage is
[A] Rs.20 [B] Rs.10 [C] Rs.50 **[D] Rs.30**
67. When Luggage is booked with passenger in the compartment it will be charged at _____
[A] Scale "R" [B] Scale "L" **[C] 1.5 times of Scale "L" rate** [D] Scale "S"
68. For booking of luggage by brake van _____ should be given at booking station.
[A] Journey Ticket [B] Application [C] Certificate **[D] F. Note**
69. Luggage ticket is prepared in _____ foils
[A] 4 [B] 2 **[C] 3** [D] 5
70. Luggage booked in Brake Van by 'R' Scale train is charged at Scale
[A] 'R' [B] 'P' [C] 'S' **[D] 'L'**
71. Luggage booked by 'S' scale train in Brake Van will be charged at _____ scale.
[A] L [B] R **[C] S** [D] P
72. Bicycles booked as luggage are charged for a minimum weight of
[A] 20 kg **[B] 40 kg** [C] 50 kg [D] 100 kg
73. In case of scooter of 150 CC, the chargeable weight is
[A] 100 kg **[B] 200 kg** [C] 250 kg [D] None of these
74. Dogs are permitted to be carried along with passengers in _____ and _____ class.
[A] I AC & SL [B] II AC & FC **[C] I AC & FC** [D] SL & ACCC
75. When dogs are offered for booking in brake van _____ should be given
[A] Ticket [B] Application [C] Certificate **[D] F. Note**
76. When dogs are booked in brake van owner must travel in the _____ train.
[A] Another [B] Any **[C] Same** [D] II Exp
77. A dog in brake van is charged for _____ KGs.
[A] 60 [B] 40 [C] 50 **[D] 30**

78. When dogs are booked in brake van chain and collar must be provided by ____
[A] Railway [B] **Owner** [C] Parcel clerk [D] None
79. Provision of food and water for animals carried in brake-van is the responsibility of ____
[A] Guard [B] Railways [C] **Owner** [D] Booking staff
80. Corpses are booked in ____
[A] With Owner [B] AGC [C] Goods Wagon [D] **BV**
81. Minimum weight for charge per corpse is ____ Kgs.
[A] 100 [B] 150 [C] 175 [D] **200**
82. Human ashes are charged for ____ Kgs.
[A] 10 [B] **20** [C] 15 [D] 5
83. Loading of parcels must be done in ____ order in the brake van.
[A] **Geographical** [B] Parallel [C] Standard [D] None
84. Parcel way bill is prepared in ____
[A] 3 foils [B] **4 foils** [C] 5 foils [D] 2 foils
85. The highest scale for charging parcels is
[A] P [B] **R** [C] S [D] L
86. A passenger without ticket or G.C. is charged
[A] **Fare + EC** [B] EC only [C] Double the fare [D] Basic fare
87. Number of concessions allowed at one time is
[A] **One** [B] Two [C] Three [D] Four
88. The element of concession allowed for female Senior Citizen
[A] 25% [B] **50%** [C] 30% [D] 75%
89. Check conducted at Mid-Section by stopping train
[A] CRB check [B] Massive Check
[C] **Ambush Check** [D] Replacement Check
90. Application for compensation in case of death due to train accident is made to ____
[A] **RCT** [B] RRT [C] HRC [D] District Court
91. Compensation payable for death of passenger in a railway accident is Rs. ____ lakhs.
[A] 4 [B] 10 [C] 6 [D] **8**
92. Compensation is not paid due to death/injury in Untoward Incident on account of
[A] Suicide [B] Self inflicted injury [C] Criminal act by passenger
[D] **All these**
93. Ex-gratia payment in case of death per passenger in a train accident is Rs. ____
[A] **50,000** [B] 25,000 [C] 10,000 [D] 5000
94. Ex-gratia paid for grievous /serious injury in train accident is ____
[A] Rs. 50,000/- [B] **Rs. 25,000/-** [C] Rs. 15,000/- [D] Rs. 5,000/-
95. Exgratia paid for simple injury in train accident is ____
[A] 25,000 [B] 10,000 [C] **5,000** [D] 1,000

96. As per Section _____ of Railway Act 1989, traveling without ticket is prohibited.
[A] 55 [B] 56 [C] 57 [D] 58
97. As per Section _____ of Railways Act. 1989, separate accommodation is provided for ladies.
[A] 164 [B] 162 [C] 58 [D] 167
98. Alarm chain is provided as means of communication between passengers and Railways as per Section _____ of Railway Act, 1989.
[A] 55 [B] 58 [C] 59 [D] 64
99. Passenger travelling without ticket can be removed from the compartment as per Section ____ of the Railways Act, 1989.
[A] 137 [B] 138 [C] 139 [D] 141
100. Male passenger found travelling in Ladies compartment is penalized as per Section _____ of the Railways Act. 1989.
[A] 164 [B] 162 [C] 58 [D] 167
-

Updated upto July, 2020

KEY FOR 25% GENERAL SELECTION OF SMs FROM PM'S IN SECUNDERABAD DIVISION									PAGE-1
S.NO	ANS	S.NO	ANS	S.NO	ANS	S.NO	ANS	S.NO	ANS
1	A	41	A	81	C	121	C	161	D
2	A	42	B	82	C	122	A	162	A
3	B	43	C	83	D	123	B	163	C
4	C	44	B	84	A	124	C	164	B
5	A	45	B	85	C	125	D	165	A
6	A	46	D	86	D	126	D	166	C
7	A	47	C	87	B	127	B	167	C
8	C	48	B	88	A	128	B	168	D
9	D	49	B	89	B	129	A	169	A
10	A	50	D	90	A	130	C	170	D
11	C	51	A	91	B	131	B	171	A
12	A	52	C	92	B	132	C	172	A
13	D	53	D	93	C	133	C	173	C
14	B	54	B	94	D	134	D	174	C
15	A	55	B	95	D	135	C	175	B
16	B	56	C	96	B	136	A	176	C
17	B	57	A	97	B	137	D	177	D
18	B	58	C	98	A	138	C	178	A
19	C	59	D	99	D	139	C	179	D
20	D	60	C	100	C	140	A	180	A
21	B	61	B	101	C	141	D	181	C
22	B	62	C	102	D	142	B	182	B
23	C	63	B	103	C	143	D	183	A
24	A	64	A	104	A	144	C	184	B
25	D	65	B	105	B	145	B	185	D
26	A	66	A	106	B	146	C	186	C
27	C	67	A	107	B	147	B	187	B
28	B	68	A	108	C	148	B	188	C
29	B	69	C	109	C	149	A	189	C
30	D	70	B	110	B	150	C	190	D
31	A	71	C	111	D	151	A	191	C
32	D	72	A	112	C	152	B	192	A
33	C	73	C	113	D	153	B	193	B
34	C	74	C	114	C	154	C	194	B
35	A	75	C	115	C	155	C	195	B
36	B	76	B	116	B	156	A	196	C
37	C	77	D	117	C	157	A	197	A
38	B	78	D	118	C	158	C	198	A
39	C	79	C	119	B	159	A	199	A
40	D	80	A	120	A	160	C	200	B

KEY FOR 25% GENERAL SELECTION OF SMs FROM PM'S IN SECUNDERABAD DIVISION									PAGE-2
S.NO	ANS	S.NO	ANS	S.NO	ANS	S.NO	ANS	S.NO	ANS
201	B	241	C	281	B	321	B	361	C
202	B	242	B	282	C	322	B	362	B
203	A	243	C	283	B	323	D	363	A
204	C	244	A	284	A	324	C	364	D
205	A	245	A	285	C	325	C	365	C
206	D	246	A	286	C	326	A	366	A
207	A	247	B	287	A	327	D	367	A
208	B	248	B	288	B	328	A	368	D
209	A	249	C	289	A	329	A	369	B
210	A	250	B	290	D	330	C	370	D
211	D	251	C	291	A	331	C	371	B
212	B	252	B	292	A	332	D	372	D
213	C	253	B	293	A	333	D	373	A
214	D	254	A	294	C	334	B	374	D
215	C	255	D	295	B	335	C	375	D
216	D	256	A	296	D	336	D	376	C
217	A	257	D	297	D	337	C	377	B
218	B	258	C	298	B	338	B	378	C
219	A	259	D	299	D	339	A	379	A
220	B	260	C	300	A	340	D	380	A
221	B	261	A	301	B	341	C	381	C
222	C	262	A	302	A	342	D	382	B
223	D	263	C	303	C	343	C	383	C
224	A	264	B	304	D	344	B	384	C
225	B	265	C	305	A	345	D	385	B
226	A	266	D	306	D	346	A	386	B
227	B	267	C	307	C	347	A	387	C
228	D	268	C	308	B	348	B	388	D
229	A	269	D	309	C	349	A	389	C
230	D	270	C	310	D	350	B	390	A
231	C	271	A	311	C	351	C	391	A
232	A	272	B	312	B	352	B	392	A
233	B	273	A	313	A	353	B	393	A
234	A	274	B	314	A	354	C	394	C
235	B	275	B	315	D	355	A	395	B
236	C	276	B	316	A	356	B	396	D
237	B	277	D	317	C	357	B	397	C
238	C	278	A	318	C	358	B	398	A
239	B	279	D	319	A	359	C	399	C
240	D	280	A	320	B	360	C	400	D

KEY FOR 25% GENERAL SELECTION OF SMs FROM PM'S IN SECUNDERABAD DIVISION									PAGE-3
S.NO	ANS	S.NO	ANS	S.NO	ANS	S.NO	ANS	S.NO	ANS
401	C	441	A	481	A	521	A	561	B
402	B	442	B	482	C	522	C	562	A
403	B	443	C	483	D	523	D	563	A
404	A	444	B	484	A	524	A	564	A
405	B	445	D	485	B	525	D	565	C
406	D	446	A	486	D	526	C	566	B
407	C	447	B	487	C	527	A	567	D
408	D	448	B	488	D	528	A	568	B
409	B	449	C	489	B	529	B	569	B
410	B	450	A	490	A	530	D	570	A
411	A	451	C	491	A	531	A	571	C
412	A	452	C	492	C	532	B	572	B
413	B	453	C	493	C	533	D	573	D
414	C	454	D	494	A	534	C	574	B
415	C	455	D	495	A	535	B	575	B
416	C	456	B	496	D	536	C	576	D
417	A	457	D	497	C	537	C	577	B
418	B	458	C	498	B	538	D	578	B
419	D	459	D	499	B	539	A	579	A
420	A	460	A	500	A	540	B	580	A
421	B	461	A	501	C	541	C	581	A
422	C	462	D	502	B	542	B	582	B
423	A	463	D	503	A	543	B	583	D
424	C	464	B	504	A	544	A	584	A
425	C	465	D	505	C	545	A	585	B
426	C	466	C	506	A	546	B	586	D
427	D	467	B	507	C	547	B	587	D
428	A	468	A	508	D	548	C	588	B
429	D	469	C	509	A	549	A	589	B
430	C	470	C	510	C	550	A	590	B
431	D	471	D	511	A	551	A	591	D
432	B	472	B	512	C	552	A	592	C
433	C	473	A	513	C	553	B	593	C
434	C	474	C	514	D	554	A	594	B
435	D	475	D	515	A	555	B	595	A
436	A	476	C	516	B	556	C	596	D
437	B	477	C	517	A	557	A	597	C
438	C	478	B	518	D	558	D	598	B
439	C	479	A	519	C	559	B	599	D
440	A	480	B	520	B	560	C	600	D

KEY FOR 25% GENERAL SELECTION OF SMS FROM PM'S IN SECUNDERABAD DIVISION									PAGE-4
S.NO	ANS	S.NO	ANS	S.NO	ANS	S.NO	ANS	OFFICIAL LANGUAGE	
601	A	641	B	681	B	26	B	S.NO	ANS
602	B	642	D	682	C	27	A	1	C
603	C	643	D	683	A	28	C	2	A
604	A	644	C	684	B	29	D	3	A
605	A	645	B	685	A	30	D	4	A
606	B	646	A	686	C	ARITHMETICS		5	C
607	A	647	C	687	A	S.NO	ANS	6	B
608	C	648	B	688	C	1	C	7	D
609	B	649	C	689	C	2	D	8	A
610	D	650	D	690	A	3	B	9	A
611	B	651	B	691	D	4	A	10	C
612	D	652	B	692	C	5	B	11	C
613	A	653	D	693	C	6	A	12	C
614	C	654	D	694	D	7	D	13	A
615	A	655	A	695	B	8	A	14	A
616	B	656	B	ESTABLISHMENT		9	C	15	C
617	C	657	D	1	C	10	A	16	C
618	C	658	D	2	C	11	C	17	A
619	D	659	B	3	A	12	B	18	A
620	B	660	B	4	B	13	C	19	B
621	C	661	C	5	A	14	A	20	C
622	D	662	B	6	C	15	A	21	C
623	C	663	C	7	D	16	D	22	C
624	B	664	B	8	C	17	B	23	A
625	C	665	D	9	C	18	B	24	B
626	D	666	B	10	A	19	D	25	D
627	C	667	C	11	C	20	C	26	C
628	D	668	A	12	D	21	D	27	C
629	A	669	D	13	A	22	A	28	A
630	A	670	C	14	D	23	C	29	B
631	A	671	D	15	C	24	B	30	B
632	B	672	C	16	B	25	B	--	--
633	A	673	A	17	A	26	A	--	--
634	B	674	B	18	B	27	A	--	--
635	C	675	C	19	C	28	A	--	--
636	D	676	C	20	D	29	C	--	--
637	C	677	A	21	A	30	C	--	--
638	A	678	C	22	C	--	--	--	--
639	D	679	B	23	B	--	--	--	--
640	A	680	A	24	B	--	--	--	--
---	--	--	---	25	A	--	--	--	--

KEY FOR 25% GENERAL SELECTION OF SMs FROM PM'S IN SECUNDERABAD DIVISION									PAGE-5
GENERAL ENGLISH& GENERAL KNOWLEDGE									
S.NO	ANS	S.NO	ANS	S.NO	ANS	S.NO	ANS	S.NO	ANS
1	B	41	C	81	D	1	A	41	A
2	B	42	A	82	C	2	B	42	A
3	B	43	A	83	D	3	A	43	B
4	B	44	B	84	B	4	B	44	B
5	A	45	A	85	C	5	C	45	A
6	B	46	C	86	D	6	D	46	B
7	A	47	C	87	C	7	A	47	A
8	C	48	C	88	A	8	A	48	B
9	B	49	A	89	B	9	C	49	C
10	C	50	B	90	D	10	B	50	B
11	A	51	A	91	A	11	A	51	D
12	B	52	C	92	C	12	C	52	B
13	C	53	D	93	A	13	A	53	C
14	A	54	A	94	D	14	D	54	D
15	C	55	D	95	B	15	A	55	B
16	A	56	B	96	A	16	B	56	A
17	B	57	C	97	C	17	C	57	A
18	A	58	A	98	C	18	D	58	C
19	C	59	C	99	C	19	A	59	B
20	C	60	A	100	B	20	B	60	D
21	C	61	B	101	D	21	C	--	--
22	B	62	D	102	A	22	B	--	--
23	A	63	A	103	C	23	B	--	--
24	B	64	C	104	B	24	D	--	--
25	C	65	D	105	D	25	A	--	--
26	C	66	C	106	A	26	B	--	--
27	B	67	D	107	A	27	A	--	--
28	A	68	A	108	D	28	A	--	--
29	C	69	C	109	A	29	C	--	--
30	A	70	D	110	C	30	C	--	--
31	C	71	C	111	C	31	D	--	--
32	B	72	B	112	B	32	D	--	--
33	A	73	D	113	D	33	A	--	--
34	C	74	C	114	C	34	A	--	--
35	C	75	D	115	B	35	B	--	--
36	A	76	B	116	A	36	A	--	--
37	C	77	C	117	C	37	A	--	--
38	B	78	A	118	A	38	A	--	--
39	B	79	B	119	B	39	A	--	--
40	B	80	C	120	D	40	D	--	--
THE END									